

NASA Powered Lift Facility Internally Generated Noise and Its Transmission to the Acoustic Far Field

(NASA-CR-182217) NASA POWERED LIFT FACILITY
INTERNALLY GENERATED NOISE AND ITS
TRANSMISSION TO THE ACOUSTIC FAR FIELD Final
Report (Sverdrup Technology) 219 PCSC 14B

N89-16882

Unclass
G3/09 0190065

Ronald G. Huff
Sverdrup Technology, Inc.
NASA Lewis Research Center Group
Cleveland, Ohio

November 1988

Prepared for
Lewis Research Center
Under Contract NAS3-25266

NASA POWERED LIFT FACILITY INTERNALLY GENERATED NOISE
AND ITS TRANSMISSION TO THE ACOUSTIC FAR FIELD

Ronald G. Huff

Ronald G. Huff and Associates
Engineering Consultants
6137 Sherwood Dr.
North Olmsted, Ohio 44070

ABSTRACT

Noise tests of NASA Lewis Research Center's Powered Lift Facility were performed to determine the frequency content of the internally generated noise that reaches the far field. The sources of the internally generated noise are the burner, elbows, valves, and flow turbulence. Tests over a range of nozzle pressure ratios from 1.2 to 3.5 using coherence analysis revealed that low frequency noise below 1200 Hz is transmitted through the nozzle. Broad banded peaks at 240 and 640 Hz were found in the transmitted noise. This (640 Hz peak) explains the apparent low frequency aircraft core engine noise peak frequency of 500 Hz observed during core engine noise studies. Aeroacoustic excitation effects are possible in this frequency range. The internal noise creates a noise floor that limits the amount of jet noise suppression that can be measured on the PLF and similar facilities.

E-4464

INTRODUCTION

Aeroacoustic excitation has been shown to increase jet mixing rates and to increase lift and decrease drag of airfoils at high angle of attack (ref. 1). This is the result of changes in the coherent (large scale) structure, random turbulence (fine scale) structure and gross mixing characteristics in shear layers due to acoustic excitation. The source of acoustic waves used in these jet experiments was placed upstream of the jet nozzle exit thus transmitting acoustic waves through the nozzle to the jet shear layer. In the NASA Lewis Powered Lift Facility (PLF) tests are performed on nozzles, ejectors and devices that are expected to turn the flow in a desired direction for thrust vectoring. Failure to account for the flow modifications due to the acoustic waves, may lead to misinterpretation of aerodynamic results. The sources of acoustic excitation in PLF are the burner, elbows, valves and turbulence generated by the flow through the pipe.

Aircraft jet engines have noise sources that are similar to those in the PLF. Noise predictions (ref. 2), for core engine noise in turbine type aircraft engines indicate that maximum noise levels occur around a frequency range of 400 to 600 Hz. The reason for the peak occurring at a frequency of approximately 500 Hz was the subject of extensive research during the 1970's

*Subcontractor to Sverdrup Technology, Inc., NASA Lewis Research Center Group, Cleveland, Ohio 44135 (Subcontract Nos. 2717-01-80 and 2717-85, R.M. Nallasamy, Contract Monitor).

and early 1980's. A major source of core engine noise was thought to be the combustor. Combustors generate noise by the turbulence generated by the flow passing through turbulence generators and flow passages (cold flow), and by the interaction of the flame front with upstream generated turbulence in the combustor reference 3. Overall sound pressure levels in excess of 170 dB have been measured in core engine combustors. In addition, under certain conditions, reflections from the turbine and compressor inside the combustor can generate tones having high amplitude (ref. 4) that could be transmitted through the engine nozzle. These noise sources exist in the PLF burner and will need to be considered.

Valve noise has been recognized as a major internal noise source. Overall sound pressure levels in excess of 160 dB have been recorded downstream of butterfly valves used to control flow in air flow piping systems (ref. 5).

The problem created by unwanted noise in the PLF is illustrated by the results reported in reference 6. Interaction of screech tones in a jet-ejector configuration with the shear layer increased the pumping of the ejector and hence its thrust. If the tones are triggered by upstream generated noise, the results of similar tests in PLF may lead to errors in the desired measurements.

To evaluate PLF acoustically and determine the extent of the PLF noise reaching the acoustic far field, noise measurements were made simultaneously with internal dynamic pressure transducers and far field microphones. Extensive use has been made of coherence analysis to determine the spectral characteristics of the sound transmitted through the nozzle. This is the sound that could affect the test configurations downstream of the nozzle and possibly modify test results.

Another important result of these tests is the evaluation of the effect of internally generated noise on the measurements made on jet noise suppressors that may be tested on the PLF. Since the internal noise creates a noise floor that limits the suppression measured on the PLF it is important to at least qualitatively evaluate the internal noise floor.

The results of these tests may be used as a guide to aid future PLF users in qualitatively evaluating possible effects of PLF internal noise on their experiments. It was also necessary to determine the internal noise so the PLF may be improved as required.

Due to the lack of necessary far field microphones, the acoustic power could not be determined. These tests were not intended to be a complete acoustic evaluation of the noise generated by PLF. They were conducted to qualitatively evaluate the rig internal noise transmitted to the far field. The following report is the result of these tests.

APPARATUS

The Powered Lift Facility (PLF) is shown pictorially in figure 1. An overview is presented in figure 1(a). Figure 1(b) shows the test stand with 12 in. standard nozzle installed. The test stand has thrust measurement capability. Figure 1(c) shows pictorial details of the nozzle installation.

Air is provided by the NASA Lewis central air handling facility through an underground piping system to a point shown at the upper right corner of the schematic shown in figure 2. A positive shutoff gate valve is located just above the ground and is used to isolate the rig from the central supply system when the rig is not in operation. When PLF is operating this gate valve is completely open and is not expected to generate significant noise levels. Following the gate valve, the flow passes through two 90° elbows and then through a venturi used to measure the mass flow rate through the facility. Very little noise should be generated by the venturi provided flow separation is not present. Downstream of the venturi, the flow encounters the first flow control valve. This butterfly valve is probably the first major source of noise in the system. Downstream of this valve, a tee allows the flow to be split between two pipes. The smaller pipe leads to an in line J57 combustor can, used to heat the air supplied to the test hardware. Downstream of the tee, a 90° elbow is installed in the smaller pipe allowing the pipe to be run parallel to the large pipe. Butterfly valves are installed in both the large and small pipes to allow the flow through each of the pipes to be independently controlled. These butterfly valves are expected to be major noise generators. The burner is also a major noise generator when flow passes through it with or without the burner flame turned on. Downstream of the burner, the bypass flow passes through a 90° elbow and rejoins the flow in the larger pipe. The merged flow passes through two 90° elbows and then to a tee located at the test stand. At the tee, the flow is split as shown in figure 2. Each half passes through two 90° elbows and then through bellows to another tee where the flow enters the floating portion of the test stand through a single pipe. The bellows were installed to isolate the test hardware from the piping leading to the floating portion of the test rig to accommodate the thrust measurement. A flow straightener is installed in the straight pipe downstream of the tee and also at the entrance to the nozzle section. No acoustic mufflers or noise suppression devices were installed in the piping to suppress the internally generated noise during these tests.

INSTRUMENTATION

Aerodynamic

Aerodynamic instrumentation provided for measurement of the air mass flow rate using a venturi installed in the main supply pipe upstream of the burner bypass pipe tee. Air total temperature and pressure were measured upstream of the nozzle. Wind direction and speed were also measured. Barometric pressure was recorded. All aerodynamic measurements were recorded using a central data processing system.

Acoustic

The acoustic instrumentation consisted of two separate systems: far field acoustic measurements using microphones and internal pipe fluctuating pressures using high sensitivity pressure transducers.

Far field. - Half-inch high stability precision pressure (random incidence) response condenser microphones having a frequency response from 4.5 Hz

to 20 kHz (\pm 2 dB) were used to measure far field noise. A 75-ft-radius microphone circle with center at a point on the ground directly under the nozzle exit was used. The microphones were taped to a 2-ft-square plywood board laid on the ground and were pointed at the nozzle exit. They were placed on the board centerline and at a point near the boards edge such that the largest distance on the board, 18 in., was between the microphone and the nozzle. The microphones were arranged around the microphone circle at 30° (microphone 1), 45° (microphone 2), 60° (microphone 3), and 90° (microphone 4) off the jet axis (fig. 3(a)). The microphone output passed through amplifiers and then to an FM tape recorder where it was recorded for off line data analysis. The gains from each microphone were recorded manually for use during data reduction. Each microphone was calibrated before and after the run using a 250 Hz, 124 dB sound pressure level Piston phone.

Internal transducers. - The pressure transducers used to measure the fluctuating wall static pressures in the pipe, were set up to read the differential pressure between the transducer face mounted flush at the inside surface of the pipe and a static pressure tap placed in the pipe near the transducer face. A long length of tubing was connected between the transducer reference side and the static tap thus damping the dynamic pressure component coming from the tap. The transducers were installed in pairs spaced 2 in. apart along the pipe axial direction (fig. 3(b)). Pairs of transducers were installed at three axial locations in the pipe: the first in the vertical pipe leading to the test rig (transducers 5 and 6), the second just downstream of the flange in the straight pipe upstream of the nozzle (transducers 7 and 8) and the third pair just upstream of the nozzle (transducers 9 and 10) (fig. 3(c)). The output from the pressure transducer was passed through a signal conditioner and then to a linear amplifier. To eliminate electrical noise in the signal a 10 kHz low pass filter was used at the amplifier. Therefore, all of the transducer data is limited to frequencies at or below 10 kHz. As with the microphones, the output from the transducer amplifiers were recorded on FM tape for off line data reduction.

DATA REDUCTION

Aerodynamic

The aerodynamic data was recorded using the central data processing facility located at NASA Lewis for post run computer processing. A computer located at this facility later reduced the data to engineering units and produced the required output. Mass flow rates were calculated as was the nozzle pressure ratio. Table I list the reading numbers, nozzle pressure ratios, total temperature (TAMB) and pressure (PTS), mass flow rate (W), ambient temperature (TAMB) and pressure (PAMB), and the wind direction and speed.

Acoustic

The acoustic data was recorded on FM tape for post run analysis.

Third octave and overall sound pressure level. - Spectral analysis was performed on a Rockland third octave analyzer and transmitted to the central data processing facility for computer processing. The third octave and overall sound pressure level data were processed and tabulated using an existing

acoustic data reduction program. The overall sound pressure level data are tabulated in table II along with the reading numbers and nominal nozzle pressure ratios.

Narrow-band and coherence function. - Narrow-band analysis were made using a Brüel and Kjaer dual channel signal analyzer, type 2032. The analyzer provided narrow-band (autocorrelation) analysis, coherence functions and phase information.

The coherence function provides a measure of the similarity between two signals. If only two signals are present and the coherence function equals unity (1.0), the signals are exactly the same. If the coherence function is zero, the two signals do not have similar time traces and are said to be uncorrelated. For coherence function values between 0 and 1, the similarity of the two signals is not as clearly defined. This is especially true when a second, strong, uncorrelated noise source is present in one of the signals. In general the data taken during these tests, that is, coherence functions between the internal pressure transducers and the far field microphones, are contaminated by the noise made by the jet mixing with the ambient air. This noise is generated outside of the pipe and is not present in the measurements made inside the pipe but is picked up by the far field microphone. When investigating the amount of internal noise reaching the far field using the coherence function between the internal pressure transducers and the far field microphones, the jet noise is a second decorrelating noise source that causes the coherence function to be less than unity. This will be discussed further in the results and discussion section of this report.

For completeness, the data as reduced from the tape recordings are shown in the appendices. Complete third octave spectral data is given in appendix A. Coherence function and phase angle plots are shown in appendix B. Appendix C contains representative cross correlations for internal to far field microphones (part I) and internal to internal pressure transducers (part II). Sample Coherent Output Power spectra and Coherence Function are shown in appendix D. Sample narrow-band Spectra are given in appendix E. For purposes of comparison, the coherence function between transducers 10 (part I) and 9 (part II) to the far field microphones are presented in appendix F. The data used to produce the figures used in the remainder of this report are taken from the appendices.

RESULTS AND DISCUSSION

As discussed in the introduction, the PLF generates noise internally at the flow control valves, the burner, at points of flow separation and along the pipe due to flow generated turbulence. To determine how much of this noise gets to the experimental test hardware downstream of the nozzles, it is necessary to determine what part passes through the nozzle and reaches the acoustic far field. Through the use of the coherence function, one can infer the spectral characteristics that two signals have in common, provided the two signals are not contaminated by other uncorrelated noise sources.

Internal to Far Field Noise

The coherence function between the internal transducer located just upstream of the nozzle (transducer 10) and the far field microphone located at

90° off the jet axis (microphone 4) is shown in figure 4 over a range of nozzle pressure ratios from 1.2 to 3.5. At pressure ratio 1.2 (fig. 4(a)), the value of coherence exceeds 0.6 at a frequency of 238 Hz. Significant coherence exist over the range of frequencies from 0 to 1000 Hz. A secondary peak coherence occurs between 400 and 600 Hz. The jet noise peak frequency based on a Strouhal number of 0.2 is 117 Hz. Since the peak coherent frequencies are well above the jet frequency, it is concluded that noise generated by the jet is not passing upstream through the nozzle thus causing an erroneous coherence between the internal and far field signals. As the nozzle pressure ratio is increased to 1.4 (fig. 4(b)), the coherence decreases at the 238 Hz frequency to 0.5 and the secondary peak also decreases. The peak jet noise frequency is 139 Hz, again well below the peak coherence frequencies. As the pressure ratio increases to near choking (1.8) the coherence decreases (fig. 4(c)), and the 238 Hz peak no longer exist. The peak coherence does, however, exist in the 400 to 800 Hz frequency range. Peak jet noise frequency is approximately 225 Hz. The peak coherence occurs at 690 Hz. Again the conclusion is that the jet noise is not a factor in the coherence function.

The coherence for pressure ratios above choking (figs. 4(d) to (f)), exhibit similar coherence functions but with lower values over the range of frequencies from 400 to 1000 Hz. A peak coherence value of between 0.15 and 0.25 is exhibited in this frequency range. At a pressure ratio of 3.5 the jet noise peaks at 330 Hz, again well below the coherence peak of 600 Hz. As has been discussed, the most probable cause of the decrease in the value of the coherence function is the decorrelating effect of the uncorrelated jet noise signal reaching the far field microphone. This is a problem that was anticipated and should not be a major concern nor detract from the results. The conclusion drawn from figure 4 is that the internal noise, measured by the internal transducer, is reaching the far field microphone throughout the range of nozzle pressure ratios tested. This conclusion applies over a range of frequencies from 0 to 1000 Hz. The frequency for peak noise transmission is in the range of 400 to 800 Hz.

This conclusion explains the early prediction of aircraft core engine noise peak frequency of 400 Hz (ref. 2). It is reasonable to expect the noise generated by the compressor, combustor and turbine to be transmitted through the core engine nozzle and subjected to the same nozzle transfer function as exists in the PLF.

Internal Noise

It is well known, that noise is attenuated as it passes through an elbow. The extent of the attenuation is a function of frequency. For random input to hard wall ducts 1 ft high, one might expect maximum attenuations on the order of 8 dB at a frequency of 600 Hz. Below 200 Hz, no transmission loss is expected and above 2000 Hz the loss is on the order of 3 dB. The one-third octave spectra for transducer number 5 located in the vertical pipe and number 10 located just upstream of the nozzle, figure 3(c) is shown in figure 5(a) as a function of nozzle pressure ratio. Over the range of pressure ratios tested, the transmission loss is relatively constant and is on the order of 40 dB. Part of this loss may be attributed to the elbows between the transducers. Four elbows or tees exist, plus two 45° turns, in the section just upstream of the nozzle. In addition, a flow straightener consisting of a honeycomb section is installed at the tee just upstream of the nozzle. If the equivalent of

five elbows are assumed the 8 dB per elbow yields the 40 dB measured value. However the large loss below 200 and that above 2000 Hz cannot be accounted for by elbow transmission loss. It is possible that another process is occurring. The flow after the vertical pipe section leading to the horizontal piping is split and then rejoined at a tee just upstream of the nozzle. Noise coming from upstream is also split and rejoined at the tee. It may be possible that the acoustic waves interfere at the tee and that their amplitude is therefore reduced.

For comparison purposes, figure 5(b) shows transducer numbers 9 and 5 spectra. Transducer number 9 is 2 in. upstream of transducer number 10. At the lower pressure ratios, both transducers 9 and 10 have similar sound pressure level differences (figs. 5(a) and (b)). An anomaly exists in the data that at this time has not been explained. Figure 5(c) shows the spectra for each internal transducer at a pressure ratio of 3.5. Transducer number 10 has a much lower sound pressure level than transducer number 9 even though they are separated by only 2 in. Analysis of the duct acoustics is complicated by reflections from the tees, elbows and nozzle that can cause standing waves in the pipe. The noise also has an unknown distribution as it enters the pipe and that further complicates analysis. Given the limited number of transducers in the pipe further analysis is not likely to provide a reason for this anomaly.

Disregarding the above anomaly, the conclusion drawn from the discussion of figure 5(a) and (b), is that transmission losses on the order of 40 dB can be produced by the elbow and flow splitting arrangement employed in the PLF. It should be pointed out that any flow separation at the elbow could create noise.

Far Field Directivity

The coherence functions for the internal transducer (number 10) to each of the far field microphones are shown in figure 6. For a nozzle pressure ratio of 1.2 (fig. 6(a)), the internal noise radiated from the nozzle appears not to be highly directional. This is consistent with the usual assumption that internally generated noise acts like a monopole source and therefore is radiated equally in all directions. However, as is evident by comparing the coherence function at the 90° to the 60° microphone location, the coherence begins to fall off slightly at the 90° location.

Comparison of figures 6(a) to (b) shows that for all microphone angles, the coherence function decreases with increasing jet velocity (pressure ratio), a result already discussed herein. Since a decrease in the coherence function is expected when jet noise is present, it should be expected that the internal to far field coherence function should be less at the angular positions where the jet noise is the greatest. Jet noise peaks at angles from 30 to 60° off the jet axis and is a function of the jet temperature, probably due to the increased jet velocity with temperature. Cold jets have peak noise closer to the jet axis than hot jets. Examination of figure 6(b) shows a minimal coherence at a frequency of 690 Hz for the 30° microphone location. The coherence is greater in figure 6(c) at the 60 and 90° locations. The same trend exists in figures 6(d) and (e). Finally, at the highest jet velocity, figure 6(f), the maximum coherence exists at the 90° location with the lower angles having much lower values by comparison. This result is expected since lower jet

noise exists at the 90° location, thus minimizing the decorrelating effect of jet noise on the internal to far field correlation. This result has extreme implications when the PLF or any jet noise test rig used for jet noise suppressor testing has internal noise present. In fact, the sideline jet noise suppressor results would be wrong causing erroneous results to be reported.

The conclusion based on this discussion is due to the directivity of jet noise, the internal noise is most likely to appear as a noise floor at the sideline measuring point, provided the jet noise has been suppressed. It is imperative that the internal noise be reduced below the acceptable sideline level for jet noise suppressor testing to avoid erroneous test results.

Internal Coherence

The internal fluctuating pressure measured by the transducer, is the resultant sum of the acoustic and turbulent pressures. Turbulence decays with distance and changes its character so that it decorrelates with relative small downstream distances. The coherence function between the upstream transducer, number 5 (upstream vertical pipe section) and the nozzle transducer, number 10 is presented in figure 7(a). The transducers are separated by large distances. Therefore the turbulence is not correlated at either of the transducers though it does exist in each of the pressure measurements. The coherence function therefore is a measure of the acoustic pressure that is transmitted along the pipe. The coherence at a pressure ratio of 1.2 and 3.5 is high at frequencies lower than 440 Hz. This is consistent with the fact that low frequencies tend to be transmitted, while higher frequencies tend to be attenuated by the elbows. The coherence has lower values above 440 Hz but exist up to frequencies on the order of 1200 Hz. The lower magnitude is probably due to elbow and geometry transmission loss.

The coherence function between the nozzle (transducer number 10) and a point 28 in. upstream of the nozzle (transducer number 7), figure 7(b), is a measure of the acoustic signal at the nozzle. The magnitude is larger than the previous comparison, figure 7(a), because little, if any, acoustic transmission loss exists in the pipe section between the transducers. The fact that the coherence function has significant magnitude over the frequency range 0 to 1600 Hz indicates that the acoustic signal is present in the pipe just upstream of the nozzle. The difference between the shape of the coherence function at the nozzle figure 7(b) and the shape of the coherence function between the nozzle and the far field microphones at low pressure ratios figure 4(a), is an indication of the nozzle transmission loss.

The conclusion, drawn from a comparison of figures 4(a) and 7(b), is that the nozzle transmits acoustic waves over the range of frequencies from 0 and 1000 Hz with a maximum between 40 and 300 Hz and secondary maximums between 400 and 800 Hz.

PLF OASPL Directivity

The directivity of the noise generated by the PLF is shown in figure 8. The overall sound pressure level (OASPL) in the acoustic far field is plotted as a function of microphone angular location from the upstream inlet axis (that is 180° minus the microphone angular location measured from the jet

axis). At subsonic (fig. 8(a)), and transonic nozzle pressure ratios, the directivity is generally uniform. Jet noise directivity is not typically uniform. This indicates that internal noise is dominating the directivity. For nozzle pressure ratios at and above 2.5 (fig. 8(b)), Mach numbers greater than 1.22, the OASPL peaks at between 120° and 135°. This is the directivity expected for jet noise and indicates the jet noise is dominating the far field measurements above pressure ratios of 2.5. This appears consistent with the coherence function results discussion of figures 4 and 6. The conclusion drawn from this discussion, is that internal noise probably dominates the far field OASPL up to a nozzle pressure ratio of 2.5.

Narrow-band Spectra

Representative narrow-band spectral data are shown in figure 9. Comparison of the coherence function at a pressure ratio of 1.2 (fig. 6(a)), to the narrow-band spectra (fig. 9(a)), shows the narrow-band spectra maximums in the same frequency range as the coherence function maximums, that is around frequencies of 240 and 640 Hz. The conclusion is that narrow-band spectra of the internally generated noise transmitted to the acoustic far field is shown in figure 9(a).

Small, supersonic jets often generate tones as a result of an acoustic feedback from the jet mixing layer to the shear layer at the nozzle exit. These tones tend to dominate the OASPL. Large nozzles such as the one used on the PLF generally do not exhibit such tones. The PLF nozzle tested, however, did generate a strong tone at 362 Hz and its harmonics as shown in figure 9(b).

The conclusion drawn from this discussion is that the internal noise transmitted to the acoustic far field is broad-banded around a frequency of 640 Hz. As the nozzle pressure ratio is increased, the jet experiences the acoustic feed back that causes a large amplitude tone to be generated at 362 Hz and multiples thereof.

Overall Sound Pressure Level

Due to the limited number of microphones used for these tests it was not possible to determine the total acoustic power generated by the facility. A comparison of the PLF noise to prediction was not attempted. However, for informational purposes, a plot of the OASPL as a function of nozzle pressure ratio is shown in figure 10. Figure 10(a) shows the far field microphone data. Above a pressure ratio of 2.5 the OASPL increases approximately 40 dB for all microphone locations. The tones account for a significant portion of the 40 dB increase.

Figure 10(b) shows the OASPL results from the internal transducer measurements. The upstream transducers (numbers 5 and 6) are not highly dependent on pressure ratio. The transducers, located in the pipe immediately upstream of the nozzle, show an increase in level around a pressure ratio of 2.5 with the exception of transducer number 10. Transducer number 10 OASPL decreases at a pressure ratio of 2.3. No explanation for transducer number ten's behavior is presently available. Comparison of the coherence function between transducer number 9 and the far field microphones and transducer number 10 to the far field microphones were made in appendix F to validate the use of transducer 10

in this report. The coherence functions were the same for both transducer 9 and 10. The conclusion then was that the use of transducer number 10 data was justified.

Internal Noise Spectra In The Far Field

The coherence function between the internal pressure transducer at the nozzle and the far field microphones indicates a range of frequencies where the internal noise reaches the far field. The decorrelating effect of the jet noise tends to mask some of the internal noise in the far field so that the value of the coherence function cannot be considered completely definitive. As shown in figure 4 broad-banded coherence exists at 240 and 700 Hz. The far field one-third octave spectra shown in figure 11(a) (square symbols) have peaks at 250 and between 630 and 4000 Hz, corresponding to band numbers 24 and 28-36. The peak at 125 Hz (band number 21) corresponds to the jet noise peak for a Strouhal number of 0.2 and nozzle diameter of 1 ft. The conclusion is that the third octave far field spectra is dominated by the internal noise at a pressure ratio of 1.2 at the 90° sideline location. As the pressure ratio is increased through 1.8, the coherence occurring in the 630 to 1000 range remains (fig. 4). The peak third octave spectra begins in this range and extends to 4000 Hz (fig. 11(a)).

Between a pressure ratio of 1.8 and 2.0, (at choking) the magnitude of the spectra drops 20 dB but its peak remains in the internal noise frequency range (630 to 4000 Hz). This drop could be the result of choking on the nozzle acoustic transfer function. As the pressure ratio is increased above 2 (fig. 11(b)), the broad-banded peak stays in the internal noise frequency range (1600 Hz) except where aeroacoustic feedback creates tones (bands numbers 26 and 29, 400 and 800 Hz filter bands respectively, see fig. 9(b) for narrow band data).

At 60° (figs. 11(c) and (d)), similar results are found. However, at 45° (fig. 11(e)), and at pressure ratios above 1.8 (fig. 11(f)), the peak sound pressure level (SPL) occurs at 315 Hz. Based on a Strouhal number of 0.2 the jet noise peaks at 330 Hz. The conclusion is that at a pressure ratio above 1.8 and microphone angles of 45° the jet noise begins to dominate. At 30° (fig. 11(g)), and pressure ratios of 1.2 and 1.4 the internal noise dominates but above 1.4 (fig. 11(h)), the jet noise dominates at the 315 Hz frequency. The conclusion is that up to a nozzle pressure ratio of 1.4 the internal noise dominates the far field SPL at microphone angles from 30° through 90°. At the 60° and 90° microphone locations, the SPL are completely dominated by internal noise. At the 30° and 45° microphone locations and above nozzle pressure ratios of 1.4 the SPL are dominated by jet noise. These conclusions are consistent with the coherence analysis of figure 6.

CONCLUDING REMARKS

It has been shown, through the use of coherence functions, that the internal noise generated in the PLF that reaches the acoustic far field has a frequency less than 1200 Hz and exhibits broad banded peaks at 240 and 600 Hz. Spectral analysis has shown that internal noise that reaches the far field exceeds the 1200 Hz and may be transmitted up to and possibly exceeding 5000 Hz. Reference 1 states that jet shear layers can be excited at Strouhal

number of 0.5 and shows graphic evidence of the result of such excitation. For the PLF the excitation frequency based on the Strouhal number of 0.5 would be on the order of 500 Hz. This frequency is close to the measured internal noise frequency and should cause alarm when planning jet type experiments for the PLF.

For experiments involving wings operating at high angles of attack, reference 1 shows that the flow attachment can be modified when the flow is excited at Strouhal number of 4. For a wing chord of 5 ft, the excitation frequency would be approximately 800 Hz or less. Again this frequency falls within the measured frequency range for the PLF. Thus, it appears that a real need exists to evaluate the effect of PLF internally generated noise on any prospective test hardware, and that steps be taken to decrease the internal noise to an acceptable level.

Another aeroacoustic effect in reference 6, is the increases of thrust due to the screech tones generated by primary nozzles in ejectors. These tones can excite the jet mixing thus increasing the ejector thrust. Since tones exist in the PLF nozzle, thrust modification could result.

Finally, as has been pointed out in this report, internal noise generated in the PLF creates a noise floor for the facility. This noise floor will prevent the testing of jet noise suppressors since when the jet noise is suppressed the internal noise floor is measured instead of the true jet noise suppression. In fact this was the case in a previous jet noise facility located in the same area as PLF some years ago. If noise of any kind is to be measured at the PLF, the internal noise must be reduced to an acceptable level.

CONCLUSIONS

1. Broad banded noise is generated in the system by air flowing through the valves, burner and associated piping.
2. Below a frequency of 5000 Hz noise is transmitted via the piping and through the nozzle to the acoustic far field over the range nozzle pressures (1.2 to 3.5) tested.
3. Coherence from the internal to far field microphones was greatest at low nozzle pressure ratios. This indicates that the coherence measurements were affected by the jet noise source acting as a second noise source observed by the far field microphones, thus causing a decreased coherence as the jet noise increased.
4. Pipe elbows and facility geometry reduce the fluctuating pressure levels by as much as 40 dB over frequency range from 50 to 10 kHz.
5. The value of the coherence function from internal to far field microphones increased with angle from the jet axis; a result that is consistent with a decrease of jet noise with angular displacement.
6. The internally generated noise below a frequency of 1600 Hz may affect the test results of any shear layer such as jets, boundary layers, flow over airfoils, and ejector mixing regions.

7. The internally generated noise creates a system noise floor that will prevent proper jet noise suppressor evaluation tests from being performed in this facility.

PLF RECOMMENDATIONS

1. Low and medium (100 through 10 000 Hz) frequency mufflers should be installed in the straight pipe section as close as possible to the nozzle.
2. The muffler must be broad banded and reduce noise in the 50 to 1600 Hz band width. Multiple mufflers in series may be required to obtain the required insertion loss.
3. The existing valves should be replaced with quiet valves that produce high frequency noise that is more easily absorbed by mufflers and lined elbows.
4. To absorb the valve generated noise, mufflers should be placed in the line just down stream of the low noise valves. This will minimize the amplification of the valve noise by the combustor.
5. One must be aware that low frequency noise is generated by combustors. Therefore when heated air is required, the low frequency mufflers will be a necessary part of the piping downstream of the combustor.

REFERENCES

1. Stone, J.R.; and McKinzie, D.J., Jr.: Acoustic Excitation - A Promising New Means of Controlling Shear Layers. NASA TM-83772, 1984.
2. Huff, R.G.; Clark, B.J.; and Dorsch, R.G.: Interim Prediction Method For Low Frequency Core Engine Noise. NASA TM X-71627, 1974.
3. Huff, R.G.: A Theoretical Prediction of the Acoustic Pressure Generated by Turbulence-Flame Front Interactions. J. Vibration, Acoustics, Stress, and Reliability in Design, vol. 108, no. 3, July 1986, pp. 315-321.
4. Huff, R.G.: The Effect of Acoustic Wave Reflections on Combustor Noise Measurements. J. Propulsion Power, vol. 2, no. 1, Jan-Feb. 1986, pp. 18-24.
5. Huff, R.G.: Noise Generated by Flow Through Large Butterfly Valves. NASA TM-88911, 1987.
6. Quinn, B.: Interactions Between Screech Tones and Ejector Performance. J. Aircraft, vol. 14, no. 5, May 1977, pp. 467-473.

APPENDIX A

ONE-THIRD OCTAVE SPECTRAL

DATA PLOTS


APPENDIX A

PART I

FAR FIELD MICROPHONE DATA

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.2, Valve # 18



ORIGINAL PAGE IS
OF POOR QUALITY

MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=1.3, Valve # 17.5




Sound Pressure Level, re. 20 MICRO Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=1.4, Valve @ 23.6


ORIGINAL PAGE IS
OF POOR QUALITY



Sound Pressure Level, re. 20 MICRO PA.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.0, Valve # 275



Sound Pressure Level, re. 20 MICRO Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.8, Valve @ 3M.S



Sound Pressure Level, re. 20 MICRO PA.

MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=2.0, Valve @ 34.5




Sound Pressure Level, re. 20 Micro Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=2.3,V valve @ 40.0A

ORIGINAL PAGE IS
OF POOR QUALITY



MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=2.3, Valve @ 40.0




Sound Pressure Level, re. 20 Micro Pa.

ORIGINAL PAGE IS
OF POOR QUALITY

MICROPHONE 1/3 OCT AVE SPL SPECTRA


Nozzle Pressure Ratio=2.5, Valve @ 40.5



Sound Pressure Level, re. 20 Micro Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=3.0, Valve # 70.8



Sound Pressure Level, re. 20 Micro Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=3.1, Valve # 103.



Sound Pressure Level re. 20 MICRO PA.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=3.5, Valve # 83.1



Sound Pressure Level, re. 20 MICRO Pa.


MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio = 1.2, valve 12.7



MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.8, V_{ave} @ 23.7A



Sound Pressure Level (re. 20 MICRO PA.)

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.8, Nozzle #27.5A



Sound Pressure Level, re. 20 MICRO Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=2.0, Valve @335A



Sound Pressure Level, re. 20 Micro Pa.


APPENDIX A

PART II

INTERNAL PRESSURE TRANSDUCER DATA


MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=1.2, Valve #13



MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.3, Valve @77.5



Sound Pressure Level, re. 20 Micro Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.4, Valve @ 23.6



Sound Pressure Level, re. 20 MICRO Pa.


MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=1.0, Valve # 275




MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=1.8, Valve @ 31.5



MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=2.3, Valve @ 40.0



Sound Pressure Level, re. 20 MICRO PA.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=2.0, Valve @ 34.5



Sound Pressure Level, re. 20 Micro Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=2.3, Valve @40.0A



Sound Pressure Level, re. 20 Micro Pa.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=2.5, Valve @40.5



Sound Pressure Level (re. 20 Micro Pa.)

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=3.0, Valve @70.8



Sound Pressure Level, re. 20 MICRO PA.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=31, Valve #103.



Sound Pressure Level (re. 20 MICRO PA).

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=3.5, Valve @63.1



Sound Pressure Level, re. 20 MICRO PA.

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.2, Valve @12.7A



Sound Pressure Level (re. 20 Micro Pa.)

MICROPHONE 1/3 OCTAVE SPL SPECTRA


Nozzle Pressure Ratio=1.8, Valve @23.7A



Sound Pressure Level, re. 20 MICRO Pa.


MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=1.8, Valve @27.5A



MICROPHONE 1/3 OCTAVE SPL SPECTRA

Nozzle Pressure Ratio=2.0, Valve @33.5A



Sound Pressure Level, re. 20 MICRO Pa.

APPENDIX B

COHERENCE FUNCTION AND PHASE

APPENDIX B

PART I

INTERNAL PRESSURE TRANSDUCERS TO FAR FIELD MICROPHONES



20 COHERENCE
 Y: 1.00
 X: 0.00Hz + 200Hz
 SETUP W22* MA, 256 LIN

INPUT MAIN Y: 463m
X: 124.75Hz

Type 2032

Page No.
22

Sign.:



Meas.
Objec:

PLF PR1?

Ch A = 1/1

Ch E = M 1

K2G176


Comments:

1. FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: 0.00Hz + 200Hz
 SETUP W22* MA, 256 LIN

20 COHERENCE
Y: 1. 00
X: 0. OHZ + 400HZ LIN
SETUP W22* #A, 256

INPUT

MAIN Y, 919m
X, 249. 5HZ



Type 2032

Page No.
20

Sign.:

51

Modes.
Object:

PLF PR12
ChA = T10
ChB = M12

RIG 176

Comments:




FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0. OHZ + 400HZ LIN
SETUP W22* #A, 256

400 Hz MAX

W20 COHERENCE
Y: 1.00
X: 0Hz + 800Hz LIN
SETUP W22 #A: 256


INPUT MAIN Y: 854m
X: 250Hz



Type 2032

Page No.
8

Sign.:



Made.
Object.

$\frac{PLF FR 1.2}{C_i A = T 10}$ $\frac{P_{PIPE} \text{ ext}}{30^\circ}$
 $C_i B = M 1$
Rdg 176

Comments:


W1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 800Hz LIN
SETUP W22 #A: 256
MAIN Y: -23. 9DEG
X: 250Hz

[20] COHERENCE

Y₁ 1.00
X₁ OHZ + 1. 6KHz
SETUP W22 #A: 256


INPUT

MAIN Y₁ 49. 1m
X₁ 476Hz



Page No.
30

Sign. :



53

Mags.
Object:

PLF PR1.2
CH A = T10
CH B = M2

Fig 17/76

Comments:



RECORDED PAGE 13
A POOR QUALITY

COHERENCE
 Y: 1.00
 X: 0Hz + 3.2kHz $\#A$: 256 LIN
 SETUP W22

INPUT


MAIN Y: 6.26m
 X: 1000Hz

Type 2032

Page No.
18

Sign.:

0 0.5k 1.0k 1.5k 2.0k 2.5k 3.0k



Meas.
Object:

P1 F PF 1.2
CHA - 110
CHB = M1

Kd 116

Comments:
Y drops at
from 800 Hz


Abnormal P
2.2k H2 116 x

1. FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: 0Hz + 3.2kHz $\#A$: 256 LIN
 SETUP W22

MAIN Y: 157.90EG
 X: 1000Hz

20 COHERENCE
Y_s 1.00
X_s OHZ + 1.6KHz LIN
SETUP W22 #A, 256

MAIN Y_s 77.4m
X_s 476Hz



Type 2032

Page No.
32

Sign.:


55

Meas.
Object:

PLF PR 1.2
 $C_A = T/10$
 $C_B = M/2$

Fig 176

Comments:



MAIN Y_s -121.9deg
X_s 476Hz
SETUP W22 #A, 256

ORIGINAL PAGE IS
OF POOR QUALITY

COHERENCE
 Y₁: 1.00
 X₁: 0Hz + 1.6kHz LIN
 SETUP W22* #A: 256


INPUT

MAIN
Y₁: 250Hz

Type 2032

Page No.
34

Sign.:




56

Meas.
Object:

P₁ P₂ L₁
h_A = 71.1
C_B = M₃
Fig 176

Comments:




EXTRA PAGE IS
IN POOR QUALITY

1 FREQ RESP H1 PHASE
 Y₁: -200 TO +200 DEG
 X₁: 0Hz + 1.6kHz LIN
 SETUP W22* #A: 256

MAIN
Y₁: 250Hz


-37.1 DEG

COHERENCE
 1.00
 X₁: 0Hz + 800Hz Y₁: 238Hz
 SETUP W22* A₁: 256 LIN



Type 2032

Page No.
26
Sign.:



Made:
Obj ect:


PLT PR 1.2
 $ChA = T/10$
 $ChB = M/4$

R4/75

Comments:
800Hz Max

COHERENCE
 Y: 1.00
 X: 0Hz + 1.6kHz LIN
 SETUP W22* #A, 256


INPUT MAIN Y₁ 54.7m
 X₁ 476Hz



Type 2032

Page No.
28

Sign.:



Meas.
Object:



PLF PR 1.2
 $\text{Ch A} = T/10$
 $\text{Ch B} = M/4$

1/26

Comments:

1. FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: 0Hz + 1.6kHz LIN
 SETUP W22* #A, 256


MAIN Y₁ 83.6DEG
 X₁ 476Hz



3.2kHz Max

20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y₁ 7.54m
X₁ 0Hz




Type 2032

Page No.
109

Sign.:

60



Meas.
Object:

PLF PR1.2
Ch 4 = T16
Ch 1 = M2

Rd 9 / B4

Comments:



MAIN Y₁ 7.54m
X₁ 0Hz

ORIGINAL PAGE IS
OF POOR QUALITY

20 COHERENCE

Y: 1.00
X: OHZ + 1.6kHz - LIN
SETUP W2 #A, 256

MAIN Y: 25.6m
X: OHZ


Type 2032

0.8

0.6
0.4
0.2
0

Page No.
111


Sign.:



Meas.
Object:

PLF PR1.3
Ch A = T10
Ch B = M2
Rdg 184



Comments:



FREQ RESP H1 PHASE INPUT MAIN Y: -180.0DEG
Y: -200 TO +200 DEG X: OHZ + 1.6kHz LIN X: OHZ
SETUP W2 #A, 256


2D COHERENCE
Y: 1.00
X: OHZ + 1. 6KHZ 256 LIN
SETUP W2 WA: 256

MAIN Y: 19. 2m
X: OHZ



20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y:
X: 0Hz



Type 2032

Page No.
115


Sign.:

Meas.
Object:


PLF PR 1.3
 $\frac{Ch A}{Ch B} = \frac{T10}{M4}$

Rdg 104


Comments:



FREQ RESP H1 PHASE INPUT MAIN Y:
-200 TO +200 DEG X: 0Hz
X: 0Hz + 1.6kHz LIN -0.1DEG
SETUP W2 #A: 256




64



20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1. 6kHz LIN
SETUP W22 #A, 256

MAIN Y₁ 46. 8m
X₁ 684Hz



Type 2032

Page No.
47

Sign.:


65

Meas.
Object:

PLF PR J.4
ChA = T/O
ChB = M2

R-177

Comments:



① FREQ RESP H1 PHASE
Y₁ -200 TO +200 DEG
X₁ 0Hz + 1. 6kHz LIN
SETUP W22 #A, 256


MAIN Y₁ 7. 7DEG
X₁ 684Hz

INPUT

MAIN Y,
X, 684Hz

COHERENCE


Y,
1.00
0Hz + 1.6kHz LIN
SETUP W22 #A, 256



Type 2032

Page No.
49

Sign. :



MAIN Y,
X, 684Hz


FREQ RESP H1 PHASE
Y, -200 TO +200 DEG
X, 0Hz + 1.6kHz LIN
SETUP W22 #A, 256

-57. 80EG

Comments:

ORIGINAL PAGE IS
OF POOR QUALITY

[20] COHERENCE
 1.00
 Y:
 0Hz + 1.6kHz MAIN Y:
 SETUP W22 X: 684Hz 90. 1m
 #A: 256 LIN



Type 2032

Page No.
51

Sign.:


67

Meas.
Object:

PLF PR14
 $\text{CH A} = \text{T 10}$
 $\text{CH B} = \text{M 4}$

Rdg 177


Comments:



1 FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: 0Hz + 1.6kHz MAIN Y:
 SETUP W22 X: 684Hz 130. 8DEG
 #A: 256 LIN

COHERENCE
 Y: 1.00
 X: 0Hz + 1.6kHz LIN
 SETUP W22* #A: 256


INPUT MAIN Y: 21.2m
 X: 684Hz



Type 2032

Page No.
36

Sign. 1



1 FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: 0Hz + 1.6kHz LIN
 SETUP W22* #A: 256

MAIN Y: 17.3DEG
 X: 684Hz

Meas.
 Object:
 $\frac{D_E}{C_D} = PR1.6$
 $C_D = T10$
 $C_H = M1$


Fig. 178

Comments:

20 COHERENCE
Y: 1.00
X: OHZ + 1.6KHZ LIN
SETUP W22 #A, 256

INPUT

MAIN Y:
X: 684Hz 38.8m



Type 2032

Page No.
44

Sign. :

Meas. 69


Object:

PLF PR 1.6
ChA = T1
ChB = M1

R19123

Comments:

Check on
Analysis
of previous
Analyzer run
at this point.



FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: OHZ + 1.6KHZ LIN
MAIN Y:
X: 684Hz -0.9DEG
SETUP W22 #A, 256

[20] COHERENCE
 Y_1 : 1.00
 X_1 : 0Hz + 1.6kHz LIN
SETUP W22 MA: 256

INPUT MAIN Y: 15.7m
 X : 684Hz



1.0

TYPE 2032

0.8

0.6

Page No.
42
Sign.:



Meds.

Object:

Off PPLC
 $\frac{1}{2} \times 17$
 $\frac{1}{2} \times 17$

17/178


Comments:

1. FREQ RESP H1 PHASE
 Y_1 : -200 TO +200 DEG
 X_1 : 0Hz + 1.6kHz LIN
SETUP W22 MA: 256

20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

INPUT

MAIN Y: 98.0m
X: 684Hz




Type 2032

Page No.
40

Sign.:

0 0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k




1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

Comments:

PLF PR16
CHA = 710
CH P = M2

Rdg 178



ORIGINAL PAGE IS
OF POOR QUALITY



Type 2032

Page No.
38

Sign.:



Meas.
Object:

PLF PR 1.6



Ch A = T10

Ch B = M4

P#9 128

Comments:



1. FREQ RESP H1 PHASE
 Y₁ -200 TO +200 DEG
 X₁ 0Hz + 1.6KHz LIN
 SETUP W22 #A: 256



Comments:

256AVGS
More Than
Average

20 COHERENCE
 INPUT X, 238Hz
 MAIN Y, 222m
 1.00
 X, 0Hz + 1.6kHz
 SETUP W22 #A, 256 LIN



Comments:
PF PPF 1.3
Ch 1 M 2
1.67


1. FREQ RESP H1 PHASE
 Y, -200 TO +200 DEG
 X, 0Hz + 1.6kHz LIN
 SETUP W22 #A, 256 LIN
 MAIN Y, 98. 8DEC
 X, 238Hz

ORIGINAL PAGE IS
OF POOR QUALITY

COHERENCE
 Y: 1.00
 X: OHZ + 1. 6KHZ LIN
 SETUP W22 #A, 256 LIN

INPUT

MAIN Y: 240m
X: 690Hz




Type 2032

Page No.
57

Sign.:

75



Meas.
Object:

PLF PR 1.9
Ch A = T10
Ch B = M3



Rdg 179

Comments:

1. FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: OHZ + 1. 6KHZ LIN
 SETUP W22 #A, 256 LIN

MAIN Y: 174. 0DEC
X: 690Hz

ORIGINAL PAGE IS
OF POOR QUALITY



20 COHERENCE
Y: 1.00
X: OHZ + 1. 6KHz LIN
SETUP W22 WA: 256

INPUT


MAIN Y:
X: 690Hz 4. 29m

Type 2032

Page No.
61

Sign. :

0 0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k



Meds.

Object:

PLF PR 1.0
 $\text{ChA} = T/10$
 $\text{ChB} = M 1$

Rd9 180


Comments:

1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: OHZ + 1. 6KHz LIN
SETUP W22 WA: 256

W2D COHERENCE
Y₁: 1.00
X₁: 0Hz + 1.8kHz
SETUP W22 #A: 256 LIN

INPUT


MAIN Y₁
X₁: 690Hz



Comments:

Meas.
Object:

H1 PR 2.0
Obj: 110
ChB: M2
Page 187





1. FREQ RESP H1 PHASE
Y₁: -200 TO +200 DEG
X₁: 0Hz + 1.8kHz LIN
SETUP W22 #A: 256 LIN

MAIN Y₁
X₁: 690Hz

Comments:


ORIGINAL PAGE IS
OF POOR QUALITY



WPO COHERENCE
Y: 1.00
X: 0.000Hz + 100Hz
SETUP W22* #A, 500

INPUT

MAIN Y: 3.85m
X: 59.000Hz



Type 2032

Page No.
73

Sign.:

Meas.


Object:

PLF PR2.0
 $C_{HA} = 1/10$
 $C_{HB} = 1/4$

Rdg 180

Comments:

Expanded freq
13720




1. FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0.000Hz + 100Hz
SETUP W22* #A, 500

MAIN Y: 57. 1DEG
X: 59.000Hz

W20 COHERENCE
Y:
1.00
X:
0.0Hz + 400Hz
SETUP W22 #A: 256 LIN

INPUT MAIN X: 236.0Hz Y: 283m




Type 2032

Page No.
71

Sign.:


8-



Comments:

Expanded Freq
Range


1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG PHASE
X: 0.0Hz + 400Hz LIN
SETUP W22 #A: 256



Type 2032

Page No.
69


Sign.:



WFO COHERENCE

Y₁ 1.00
X₁ 0Hz + 1.6kHz MAIN Y₁ 288m

X₂ 0Hz + 1.6kHz LIN
SETUP W22 WA 256



Type 2032

Page No.
67

Sign.:




Meas.

Object:


P/F PR 2.0
Ch A = T10
Ch B = M4

Pdg /30


Comments:



1. FREQ RESP H1 PHASE
Y₁ -200 TO +200 DEG
X₁ 0Hz + 1.6kHz -112.10EG
SETUP W22 WA 256 LIN
MAIN Y₁ 694Hz




Type 2032
Page No.
93



W2D COHERENCE


Y: 1.00
X: 0Hz + 1. 6kHz LIN
SETUP W2 #A: 256 LIN



Type 2032

Page No.
95



Sign.:



85

Mass.
Object:PLF PR 2.25
Ch A T10
Ch B M2Rdg 182

Comments:

ORIGINAL PAGE IS
OF POOR QUALITY

MAIN Y,
X, OHZ 3.42m

W20 COHERENCE
Y: 1.00
X: OHZ + 1.6KHZ LIN
SETUP W2 #A: 256

1.0

Type 2032


0.8

0.6

Page No.
97

0.4


0.2



86

Meds.
Obj ect:

2.1 P
110
111
112
113
114
115
116



MAIN Y,
X: OHZ -179.50deg

1 FREQ RESP H1 PHASE INPUT
-200 TO +200 DEG
Y: OHZ + 1.6KHZ LIN
X: OHZ + 1.6KHZ LIN
SETUP W2 #A: 256


Comments:

ORIGINAL PAGE IS
OF POOR QUALITY

W20 COHERENCE

Y: 1.00
X: 0Hz + 1.6KHz LIN
SETUP W2 #A: 256

MAIN Y:
X: 0Hz 3.30m





Page No.
99

Sign.:
+

Meas.:



Object:
PLF 18
C15 MA
Rig 12

Comments:



1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1.6KHz LIN
SETUP W2 #A: 256

MAIN Y:
X: 0Hz -0.3DEG



20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y₁ 4.96m
X₁ 0Hz

Type 2032
Page No.
103

Sign.:


89

FREQ RESP H1 PHASE
Y₁ -200 TO +200 DEG
X₁ 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

Comments:


PLF PR2.5
Ch A = T10
Ch B = M2

Rd 9/03




2D COHERENCE
Y: 1.00
X: 0HZ + 1. 6KHZ LIN
SETUP W2 MA: 256

MAIN Y: 904U
X: 0HZ




Page No.
105

Sign.:
0.2 0.4 0.6 0.8 1.0 1.2k 1.4k 1.6k




Comments:
90



ORIGINAL PAGE IS
OF POOR QUALITY

20 COHERENCE
Y: 1.00
X: 0Hz + 1. 6kHz LIN
SETUP W2 #A: 256

MAIN Y: 4. 19m
X: 0Hz



91


PLF PHASE

Ch A = T10

Ch B = M9

R19/83




Comments:



1 FREQ RESP H1 PHASE INPUT MAIN Y: -179. 1 DEG
Y: -200 TO +200 DEG
X: 0Hz + 1. 6kHz LIN
SETUP W2 #A: 256

20 COHERENCE
Y: 1.00
X: 0HZ + 1.6KHZ LIN
SETUP W2 AA: 256


MAIN Y: 17.0m
X: 0HZ



ORIGINAL PAGE IS
OF POOR QUALITY

20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y: 1.5dm
X: 0Hz




Type 2032

Page No.
122

Sign.:

93

0 0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k



Meas.
Object:

PLF PR30
Ch A = 710
Ch B = M2

Rdg 105

Comments:


1 FREQ RESP H1 PHASE INPUT
Y: -200 TO +200 DEG
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y: 1.5dm
X: 0Hz


ORIGINAL PAGE IS
OF POOR QUALITY

20 COHERENCE
Y_i 1.00
X_i OHZ + 1.6kHz LIN
SETUP W2 #A1 256

MAIN Y_i 913u
X_i OHZ




Page No.
119



Mags.
Object:

PLF PR 3.0
C1 A 711
C1 E M2
K1 J185

Comments:



FREQ RESP H1 PHASE INPUT
Y_i -200 TO +200 DEG
X_i OHZ + 1.6kHz LIN
SETUP W2 #A1 256

MAIN Y_i -178.9DEG
X_i OHZ

20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1.6kHz
SETUP W2 #A: 256 LIN

MAIN Y,
X, OHZ 22.6μ

Type 2032

0.8

0.4

0.2

0.8

0.4

0.2

0.8

0.4

0.2

0.8

0.4

0.2

0.8

0.4

0.2

0.8

0.4

0.2

0.8

0.4

0.2


0.8

0.4

0.2

Page No.
117

Sign.



Mass.
Object.

PLT PP30
Ch A = 7/6
Ch B = 1/4
Rdg 195

Comments:



FREQ RESP H1 PHASE INPUT MAIN Y,
Y, -200 TO +200 DEG INPUT X, OHZ
X, 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

20 COHERENCE
Y: 1.00
X: 0Hz → 1.0kHz
SETUP W2 → 1.0kHz #A: 256 LIN



MAIN Y:
X: 0Hz

Type 2032

Page No.
125

Sign. :

0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k




Meas.
Object:

PLF PR 3.1
Ch A = T/J
Ch B = M12

9-19 196

Comments:

ORIGINAL PAGE IS
OF POOR QUALITY



1 - 2



Type 2032

Page No.
4

Sign.:



98

Meas.
Object:


PLF PR S.

Ch A: T10


Ch B: M3

196

Comments:




1. FREQ RESP H1 PHASE
Y₁: -200 TO +200 DEC
X₁: 0HZ + 1. 0KHZ
SETUP W2 #A: 256 LIN



W20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

INPUT MAIN Y: 2.42m
X: 944Hz




Type 2032

Page No.
75



Sign.:



Meds.

Obj ect:

PLF PR 3.5

ChA=T/O

ChB=M2

Rd9/87

Comments:




MAIN Y:
X: 944Hz

1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

COHERENCE
Y: 1.00
X: 0Hz + 1. 6kHz
SETUP W22 #A: 256 LIN

INPUT

MAIN Y: 6. 35m
X: 944Hz



Type 2032

Page No.
77

Sign.:



Meas.

Object:

PLF PR 3.5


Ch A = T10

Ch B = M2

Rig 187



Comments:

101



1. FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1. 6kHz
SETUP W22 #A: 256 LIN


MAIN Y: 944Hz
X: 6. 35m



WFO COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

INPUT


MAIN Y:
X: 704Hz 103m



Type# 2032

Page No.
81

Sign.:



Meas.
Object:

BLF PR3.5
ChA = T10
ChB = M4

Rd9/18/77

Comments:

1. FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

APPENDIX B


PART II

INTERNAL TO INTERNAL PRESSURE TRANSDUCERS

COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

INPUT


MAIN X: 380Hz 808m



Type 2032

Page No.
23

Sign.:




FREQ RESP H1 PHASE
Y: -200 TO +200 DEC
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

Meas.
Object:

PLF PR1.2
 $\frac{ChA = +10}{ChB = +5}$

Rd9 176


Comments:



Type 2032

Page No.
62

Sign.:





Mass.
Object.

1.07 1.12
1.15 1.10
1.13 1.17

1.61 1.66


Comments:



W20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz
SETUP W22 #A: 256 LIN

INPUT

MAIN Y: 396Hz
X: 773m



Type 2032


Page No.
83

Sign.:

Mags.

Object:

PLF PR 3.5
Ch A = T 10
Ch B = T 7



Comments:

1. FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

Rdg 187

APPENDIX C


SAMPLE CROSS-CORRELATIONS, SIGNAL DELAY INFORMATION

APPENDIX C

PART I

INTERNAL PRESSURE TRANSDUCERS TO FAR FIELD MICROPHONES

WS CROSS CORR REAL INPUT MAIN Y_i -656μ
 Y_i 9.82m X_i -178.46ms
 X_a 26.61ms #A, 256



Type 2032

Page No.
 71 6/17/93
 Sign. :

Meas.
 Object:

PLF PR 3.5
 $\frac{\text{Ch A} = \text{T9}}{\text{Ch B} = \text{M2}}$
 $\frac{\text{Time delay}}{\text{0 ms}}$
 $\frac{\text{Rds / 87}}{\text{}}$

30m 40m 50m 60m 70m 80m 90m 100m 110m 120m 130m 140m 150m

SETUP W12

MEASUREMENT:
 TRIGGER,
 DELAY,
 AVERAGING:


FREQ SPAN:
 CENTER FREQ:
 WEIGHTING:

Comments:

$\frac{\text{Acoustic delay}}{\text{time interval}}$
 $\frac{\text{to Far Field}}{\text{15' 75ft / 100ft/s}}$
 $\frac{\text{.068 sec = 68ms}}{\text{}}$
 CH. A:
 CH. B:
 GENERATOR:

1V + 3HZ DIR FILT: 25.6KHZ 1V/V
 2V + 3HZ DIR FILT: 25.6KHZ 1V/V
 RANDOM NOISE OFF

Type 2032
Paga No.
 72 6/17/98
Sign. +
Meas.
Objact:
DLF PR 3.5
Ch A = T9
Ch B = M4
Time delay
0 ms
Rds 187



112

Comments:
FREQ SPAN:
CENTER FREQ:
WEIGHTING:

DLF PR 3.5
Ch A = T9
Ch B = M4
Time delay
0 ms

Comments:
CH. A:
CH. B:
GENERATOR:

REAL
INPUT
MAIN Y₁ 5. 14m
X₁ 14. 09ms + 125ms
MAIN Y₂ 5. 14m
X₂ 78. 36ms
Meas.
Objact:
SETUP W12
MEASUREMENT:
TRIGGER,
DELAY,
AVERAGING,
FREQ SPAN:
CENTER FREQ:
WEIGHTING:
Comments:
CH. A:
CH. B:
GENERATOR:

REAL
INPUT
MAIN Y₁ 5. 14m
X₁ 14. 09ms + 125ms
MAIN Y₂ 5. 14m
X₂ 78. 36ms
Meas.
Objact:
SETUP W12
MEASUREMENT:
FREE RUN
CH. A+B, 0. 00ms
LIN 256 OVERLAP: MAX
Comments:
CH. A:
CH. B:
GENERATOR:

APPENDIX C


PART II

INTERNAL TO INTERNAL PRESSURE TRANSDUCERS

W13 CROSS CORR
Y: 14.6m
X: -31.250ms + 15.6ms
SETUP W2* #A, 256

INPUT MAIN Y: -14.6m
X: -21.911ms

Type 2032



Page No.
26

Sign.:

Meas.
Object:

PLT PPL?
Ch 1 710
Ch 2 TE

Comments:
14.6

ORIGINAL PAGE IS
OF POOR QUALITY

MEASUREMENT: DUAL SPECTRUM AVERAGING

FREE RUN

CH. A+B: 0.000ms

LIN 256 OVERLAP: MAX

SETUP W2

TRIGGER:

DELAY:

AVERAGING:

MAX

FREQ SPAN:

12.8kHz BASEBAND
HANNING

CENTER FREQ:

WEIGHTING:

CH. A:

CH. B:

GENERATOR: DISABLED
PLOT: #27, Y SCALE LINES..... FEW

ΔF: 16Hz

ΔT: 62.5ms


DIR

DIR

FILT: 25.6kHz 1V/V

FILT: 25.6kHz 1V/V

FEW



Type 2032

Page No.
63

Sign.:

115 Meas.
Object:

PF F F 1.2
CP A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

-250m -200m -150m -100m -50m 0 50m 100m 150m 200m 250m

SETUP W12


MEASUREMENT:
TRIGGER,
DELAY,
AVERAGING,
FREQ SPAN:
CENTER FREQ:
WEIGHTING:

Comments:

DUAL SPECTRUM AVERAGING
FREE RUN
CH. A+B: 0.00ms
LIN 256 OVERLAP, MAX
1. 6KHZ BASEBAND
HANNING
CH. A: 2V + 3HZ DIR FILT: 25. 6KHZ 1V/V
CH. B: 1V + 3HZ DIR FILT: 25. 6KHZ 1V/V
GENERATOR: RANDOM NOISE OFF
PLOT: #27, Y SCALE LINES..... FEW

ORIGINAL PAGE IS
OF POOR QUALITY

W1.3 CROSS CORR REAL
Y: 153m X: -250. 00ms + 500ms
X: -250. 00ms + 500ms #A: 256



Type 2032

Page No.
54

Sign. 1

116

Mass.
Object:

PLF PR 3.5
 $\frac{Ch\ A = T10}{Ch\ B = T5}$

-150m -200m -150m -100m -50m 0 50m 100m 150m 200m 250m

SETUP W12

MEASUREMENT:
TRIGGER:
DELAY:
AVERAGING:


DUAL SPECTRUM AVERAGING

FREE RUN
CH. A+B, 0. 00ms
LIN 256 OVERLAP, MAX

Comments:

FREQ SPAN,
CENTER FREQ,
WEIGHTING,
BASEBAND
HANNING
1. 6KHZ ΔF, 2Hz
T, 500ms ΔT, 244μs
CH. A, 1V + 3Hz DIR FILT, 25. 6kHz
CH. B, 2V + 3Hz DIR FILT, 25. 6kHz
GENERATOR, RANDOM NOISE OFF
PLOT, #27, Y SCALE LINES..... FEW

W:3 CROSS CORR
Y₁ 1.00
X₁ -500.00ms + 1s
#A: 256



Type: 2032

Page No.
91
Sign.:

Mode:
Object:
PLF PR 3.5
 $\frac{Ch\ A = T10}{Ch\ B = T7}$

SETUP W22

MEASUREMENT,
TRIGGER,
DELAY,
AVERAGING:

FREQ SPAN,
CENTER FREQ,
WEIGHTING,

CH. A:
CH. B:
GENERATOR,
PLOT, #27,

DUAL SPECTRUM AVERAGING
FREE RUN
CH. A → B, 0. 00ms
LIN 256 OVERLAP: MAX

800HZ BASEBAND
HANNING

1.5V + 3Hz DIR
800mV + 3Hz DIR
REFERENCE SINE
Y SCALE LINES.....

T, 1s ΔT, 488μs

117


FILT, 25. 6kHz
OFF FILT, 25. 6kHz
57. 3V/UNIT
999mV/UNIT

FEW

Rdg/187

Comments:

W1.3 CROSS CORR
Y₁ 834m
X₁ -15.625ms \rightarrow 31.3ms
#A: 256



SETUP W2

MEASUREMENT:
TRIGGER,
DELAY,
AVERAGING,
FREQ SPAN,
CENTER FREQ,
WEIGHTING,

DUAL SPECTRUM AVERAGING
FREE RUN
CH. A \rightarrow B, 0.000ms
LIN 256 OVERLAP, MAX

Comments:

KD2176 T: 31.3ms Δ T: 15.3ms

FILT: 25.6kHz
DIR FILT: 25.6kHz
DIR FILT: 25.6kHz
DIR
DISABLED
PLOT: #27, Y SCALE LINES, FEW

APPENDIX D

SAMPLE COHERENT OUTPUT POWER SPECTRA

COHERENCE
 Y: 1.00
 X: 0Hz + 1.6kHz LIN
 SETUP W22 #A: 256


INPUT

MAIN Y:
X: 476Hz

Type 2032

Page No.
31

Sign.:



Meds.
Object:

PLE PR 1.2
ChA = T10
ChB = M1

R#9176

Comments:




MAIN Y:
X: 476Hz

2 COHERENT POWER
Y: 150mV²
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

20 COHERENCE
Y: 1.00
X: 0.00Hz + 200Hz LIN
SETUP W22* #A, 256

INPUT
MAIN Y: 463m
X: 124.75Hz



Type 2032

Page No.
23

Sign.:

121

Meds.
Objact:

PLF PR 1.2
CHA = T10
CHB = M1


Rtg 176

Comments:


ORIGINAL PAGE IS
OF POOR QUALITY

2 COHERENT POWER
Y: 150m²
X: 0.00Hz + 200Hz LIN
SETUP W22* #A, 256

MAIN Y: 2.29μa
X: 124.75Hz



20 COHERENCE
 Y: 1.00
 X: 0.0Hz + 400Hz LIN
 SETUP W22* MA: 256



Type 2032

Page No.
21

Sign.:

122

Meas.
Object:

PLF PR 1.2
Ch A T1/2
Ch B M1



Ed 1/2

Comments:

ORIGINAL PAGE IS
OF POOR QUALITY

MAIN Y: 91.9m
 X: 249.5Hz
2 COHERENT POWER PWR 80dB
 Y: 150mV
 X: 0.0Hz + 400Hz LIN
 SETUP W22* MA: 256

400Hz MA



Mass.
Object!



$$\begin{array}{l} \text{PLF PR 1.2} \\ \text{ChA = +10} \\ \text{ChB = M1} \end{array}$$


ORIGINAL PAGE IS
OF POOR QUALITY

123


20. COHERENCE
Y: 1.00
X: OHZ + 1.6KHZ LIN
SETUP W22 #A, 256

INPUT MAIN Y: 726m
X: 250Hz





20 COHERENCE
1.00
Y.
X.
0Hz + 3.2kHz LIN
SETUP W22 #A: 256



Type 2032

Page No.
24

Sign.:

Made.
Object:

PLF PR 1.2
Ch A = T 12
Ch B = 14


Rk 176

Comments:

2 COHERENT POWER 80dB
Y.
X.
150mU² PWR 80dB
0Hz + 3.2kHz LIN
SETUP W22 #A: 256
3.2R/2 Max

[20] COHERENCE
Y: 1.00
X: OHZ + 1. 8kHz LIN
SETUP W22* #A: 256


INPUT MAIN Y: 54. 7m
X: 476Hz



Type 2032

Page No.
29

Sign.:



Meas.
Object:

PLF PR 1.2
Ch A = T10
Ch B = M4

Rdg 176

Comments:



ORIGINAL PAGE IS
OF POOR QUALITY

20 COHERENCE
Y: 1.00
X: 0Hz + 800Hz LIN
SETUP W22* #A: 256

MAIN Y: 849m
X: 238Hz

Type 2032

Page No.
27
Sign.:



Meas.
Object:

PLF PR 1.2
 $\frac{Ch A = T/10}{Ch B = M/4}$

Rdg 176


Comments:

2 COHERENT POWER 80dB []
Y: 150mV² PWR 80dB LIN
X: 0Hz + 800Hz LIN
SETUP W22* #A: 256

200Hz Mix

20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y:
X: 0Hz 7.54m



Type 2032

Page No.
110

Sign.:

Meds.
Obj ect:

PLF PR 1.3
Ch A = T10
Ch B = M1

Rdg 107

Comments:

2 COHERENT POWER [] INPUT
Y: 150mV² PWR 80dB
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y:
X: 0Hz 42.8E-9V²

20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y: 25.6m
X: 0Hz

Type 2032

Page No.
112

Sign.: 0

Mags.

Object:

$$\frac{PL F}{Ch A} = \frac{716}{M2}$$


PL 189

Comments:



ORIGINAL PAGE IS
OF POOR QUALITY

20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256



Page No.
114




Sign.:
114

Meas.
Object:

PLF PR 1.3
 $\frac{Ch A = T10}{Ch B = M3}$

Rdg 189

Comments:






20 COHERENCE
1.00
Y₁: OHZ + 1. 6KHZ LIN
SETUP W2 MA: 256

MAIN Y₁: 2. 64m
X₁: OHZ

Type 2032

Page No.
116

Sign.:



ORIGINAL PAGE IS
OF POOR QUALITY

Meas.
Object:


PLF PR1.3
ChA = T10
ChB = M4

Rtg. 184

Comments:

[REDACTED]


20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1.6kHz
SETUP W22 #A, 256 LIN



Type 2032

Page No.
46

Sign. :



Meas.
Object:

PLF PR 1.4

ChA = T10



ChB = M2

Ridge

Comments:


2 COHERENT POWER
Y₂ 150mV²
X₂ 0Hz + 1.6kHz
SETUP W22 #A, 256 LIN

MAIN Y₂ 684Hz
X₂ 684Hz



ORIGINAL PAGE IS
OF POOR QUALITY


COHERENCE
 X: 1.00 OHZ + 1.6KHZ 256 LIN
 X: MAIN 684HZ 90. 1m
 INPUT X: MAIN 684HZ 90. 1m





Type 2032
 Page No.
 52
 Sign.:
 Meas.


Objact:
 PLF PR14
 $\frac{CBA}{CBA} = \frac{710}{M4}$
 Pg 177

Comments:



ORIGINAL PAGE IS
 OF POOR QUALITY





20

COHERENCE

1.00

Y:
0Hz + 1.6kHz

X:
SETUP W22 #A: 256

LIN


INPUT

MAIN Y:
684Hz

X:
0Hz + 1.6kHz

LIN

98.0m



Type 2032

Page No.
41

Sign.:

Meas.
Object:


P.I.F PR 1.6
Ch A = T10
Ch B = M3
Ph 178

Comments:



ORIGINAL PAGE IS
OF POOR QUALITY

[20] COHERENCE
Y: 1.00
X: OHZ + 1. 6KHz LIN
SETUP W22 #A: 256



Type 2032

Page No.
39

Sign.:

Meas.
Object:

PLF PR 1.6
 $\frac{ChA}{ChB} = 1/10$

Rg178

Comments:

2 COHERENT POWER
Y: 150mU² PWR 80dB
X: OHZ + 1. 6KHz LIN
SETUP W22 #A: 256

INPUT MAIN Y: 947E-9U²
X: 684Hz


20

COHERENCE

Y_i 1.00
X_i 0Hz + 1. 6kHz LIN
SETUP W22 #A: 256

INPUT

MAIN Y_i 152m
X_i 238Hz



Type 2032

Page No.
54


Sign.:

Mesas.
Object:

PLF PR 1.8
Ch A = T10
Ch B = M1


Rd 9 179


Comments:



2 COHERENT POWER
Y_i 150mV
X_i 0Hz + 1. 6kHz LIN
SETUP W22 #A: 256

MAIN Y_i 1.46μJ²
X_i 238Hz






Type 2032

Page No.
58

Sign. 1



Meas.
Object:


Plt PR1.8
 $\frac{ChA}{ChB} = 115$

Plt 177

Comments:

COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W22 #A, 256

INPUT MAIN Y, 169m
X, 690Hz



Type 2032

Page No.
60

Sign.:



Mass.
Object:

PLF PR 1.8
 $\frac{Ch A}{Ch B} = \frac{T1C}{M4}$

Rdg 179

Comments:




MAIN Y, 105μa
X, 690Hz

COHERENCE
Y: 1.00
X: 0Hz + 1. 6kHz LIN
SETUP W22 #A: 256

INPUT


MAIN Y:
X: 690Hz



Type 2032

Page No.
62

Sign. :




Meas.
Object:

PLF PR2.0
 $\frac{Ch\ A = T10}{Ch\ B = M1}$

Rdg 180

Comments:




2 COHERENT POWER
Y: 150mV² PWR 80dB
X: 0Hz + 1. 6kHz LIN
SETUP W22 #A: 256

MAIN Y:
X: 690Hz

W2D COHERENCE
Y: 1.00
X: 0Hz + 1. 6kHz
SETUP W22 #A: 256 LIN

INPUT

MAIN Y:
X: 690Hz 13. 1m



Type 2032

Page No.
64


Sign.:

Meas.
Object:

PLF PR2.0
ChA = T10
ChB = M2

Rdg 180

Comments:




2 COHERENT POWER
Y: 150mJ PWR 80dB
X: 0Hz + 1. 6kHz
SETUP W22 #A: 256 LIN

MAIN Y:
X: 690Hz 3. 74μJ

W20 COHERENCE
Y, 1.00
X, 0Hz + 1.6kHz LIN
SETUP W22 #A, 256

INPUT
MAIN Y, 16. 6m
X, 690Hz



Type 2032


Page No.
66

Sign.:

Mac's.
Object:

146

ORIGINAL PAGE IS
OF POOR QUALITY



MAIN Y, 3. 18uV
X, 690Hz

2 COHERENT POWER 80dB
Y, 150Mu² PWR 80dB
X, 0Hz + 1.6kHz LIN
SETUP W22 #A, 256

Comments:

W20 COHERENCE


Y:
1.00

X:
0Hz + 1.6kHz

SETUP W22 MA: 256 LIN

INPUT

MAIN Y:
694Hz 288m



Type 2032

Page No.
68


Sign.:



Mags.
Object:

PLF PR 1.0
CH1 = T10
CH2 = M4

Rigs 180

Comments:






W20 COHERENCE

Y₁: 1.00
 X₁: 0.0Hz + 400Hz LIN
 SETUP W22 #A: 256

INPUT


MAIN Y₁: 236.0Hz
 X₁: 283m



Modes:
 Objext:
 $\frac{PLF}{ChA} = T \frac{10}{M2}$
 $\frac{ChB}{M1}$

Rdg 180


Comments:



W20 COHERENCE
 Y, 1.00
 X, 0Hz + 800Hz #A, 256
 SETUP W22* #A, 256

INPUT

MAIN Y, 337m
X, 694Hz



Type 2032

Page No.
70

Sign.:

Meds.
Objact,

P.D. Pk L
1.11 1.11
1.11 1.11

1.11 1.11
1.11 1.11

Comments:
1.11 1.11
1.11 1.11




COHERENT POWER
 Y, 150m² PWR 80dB
 X, 0Hz + 800Hz LIN
 SETUP W22* #A, 256

ORIGINAL PAGE IS
OF POOR QUALITY

W20 COHERENCE
Y₁: 1.00
X₁: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

MAIN Y₁: 42.4μ
X₁: 0Hz



Type 2032

Page No.
94


Sign.:

Made.
Object.
PLF P_E < 25
CHA-T10
CHE-MJ
RH182

Comments:

ORIGINAL PAGE IS
OF POOR QUALITY


151



2 COHERENT POWER PWR 80dB [] INPUT
Y₂: 150mV₂
X₂: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

W2D COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz 256 LIN
SETUP W2 #A: 256

MAIN Y: 1.56m
X: 0Hz



Type 2032

Page No.
96

Sign.:



Meas.
Object:

$$\frac{PLF}{Ch A} = T/0$$
$$Ch B = M/2$$


PLF 2.25

PLF 1.92

Comments:




W2C COHERENCE
Y: 1.00
X: OHZ + 1. 6KHZ
SETUP W2 #A: 256 LIN



Type 2032

Page No.
98

Sign.:




Meas.
Object:

PLF PR 2.25
CH A = T10
CH B = M3


Rd 182

Comments:



② COHERENT POWER [] INPUT
Y: 150mV² PWR 80dB
X: OHZ + 1. 6KHZ LIN
SETUP W2 #A: 256

W2D COHERENCE
Y: 1.00
X: OHZ + 1.6KHZ LIN
SETUP W2 #A: 256



ORIGINAL PAGE IS
OF POOR QUALITY

Type 2032

Page No.
100

Sign.:

154

Meas.

Object:

PA 725

PA - TIA

blk - MG

PA 122

Comments:

MAIN Y:
X: OHZ 3.30m

MAIN Y:
X: OHZ 1.6K

INPUT MAIN Y:
X: OHZ 1.2K

INPUT MAIN Y:
X: OHZ 1.4K

INPUT MAIN Y:
X: OHZ 1.6K

INPUT MAIN Y:
X: OHZ 1.2K

INPUT MAIN Y:
X: OHZ 1.4K

INPUT MAIN Y:
X: OHZ 1.6K



INPUT MAIN Y:
X: OHZ 1.2K

INPUT MAIN Y:
X: OHZ 1.4K

INPUT MAIN Y:
X: OHZ 1.6K

② COHERENT POWER PWR 80dB [] INPUT MAIN Y:
Y: 150mV₂ PWR 80dB X: OHZ 976E-12V₂
X: OHZ + 1.6KHZ LIN
SETUP W2 #A: 256

20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256




ORIGINAL PAGE IS
OF POOR QUALITY

PLT PR 2.5
Ch A = T10
Ch B = M2

RJG 183

Comments:


2D COHERENCE
Y: 1.00
X: OHZ + 1. 6KHZ LIN
SETUP W2 #A: 256



Type 2032

Page No.
104

Sign.:



Mos.
Obj ect:

PLF PR 2.5
Ch A = T10
Ch B = M2

Rd9 183

Comments:



② COHERENT POWER [] INPUT
Y: 150mV² PWR 80dB
X: OHZ + 1. 6KHZ LIN
SETUP W2 #A: 256

20 COHERENCE
Y: 1.00
X: OHZ + 1. 6kHz


SETUP W2 #A: 256 LIN

MAIN Y:
X: OHZ 904μ

Type 2032

Page No.
106

Sign.:




Meds.
Object:

PLF PR 2.5
 $\frac{Ch A = T}{Ch B = M} \frac{10}{3}$

Rdg 183

Comments:

COHERENT POWER PWR 80dB [] INPUT
Y: 150mV² X: OHZ + 1. 6kHz LIN
SETUP W2 #A: 256



Page No.

108

Sign.:


0 0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k

Meas.
Object:

PLT Pt 2.5
CVA 113
CP 14


PLT 183

Comments:



20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1.6kHz LIN
SETUP W2 #A, 256


MAIN Y: 17.0m
X: DHZ



Type 2032

Page No.
124

Sign.:



Mass.
Object:



DLF PR 3.0
Ch A = T10
Ch B = M1

Rdg 195

Comments:


159

ORIGINAL PAGE IS
OF POOR QUALITY



2 COHERENT POWER PWR 80dB [] INPUT
Y₁ 150mV₂ PWR 80dB
X₁ 0Hz + 1.6kHz LIN
SETUP W2 #A, 256

MAIN Y: 7.96E-9V
X: DHZ



Type 2032

Page No.
121

Sign.:

Mode:
Object:


PLF PR 3.0
 $\frac{C_1 A = T/10}{C_1 B = M/2}$

Rdg 18.5

Comments:

160

RECORDED PAGE 121
BY RICK VANDENBERG



20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1.6kHz LIN
SETUP W2 #A, 256

MAIN Y₁ 913u
X₁ 0Hz

Type 2032
Page No.
120

Sign. 1
1m

161




Mass.
Object.

DLE PR 3.0
Ch A = T10
Ch B = M2

Rdg 185

Comments

ORIGINAL PAGE IS
OF POOR QUALITY



20 COHERENCE
Y: 1.00
X: 0HZ + 1.6KHZ LIN
SETUP W2 #A: 256

MAIN Y: 22.6J
X: 0HZ

Type 2032

Page No.
118

Sign.:


Meds.

Object:

PLF PR 3.0
 $\frac{1.6}{1.0} = \frac{1.6}{1.0}$
B = M9

Ag 195

Comments:



162

ORIGINAL PAGE IS
OF POOR QUALITY



[2] COHERENT POWER PWR 80dB
Y: 150mV²
X: 0HZ + 1.6KHZ LIN
SETUP W2 #A: 256

MAIN Y: 893E-15V²
X: 0HZ

20 COHERENCE
Y: 1.00
X: 0Hz + 1.0kHz
SETUP W2 #A: 256 LIN

MAIN Y: 613μ
X: 0Hz

Type 2032

Page No.
126

Sign.:

Mass.
Object:

PLF PR 3.1
 $\frac{ChA = 710}{ChB = 712}$

Rdg 186

Comments:

ORIGINAL PAGE IS
OF POOR QUALITY



20 COHERENCE
Y: 1.00
X: 0Hz + 1.0kHz #A: 256 LIN
SETUP W2

MAIN Y: 7.00m
X: 0Hz

Type 2032

Page No.
2

Sign.:



Meds.
Object:


PLF PR 3.1
 $\frac{Ch A = T1D}{Ch B = M2}$

Rdg 186

Comments:


② COHERENT POWER 80dB [] INPUT
Y: 150mVc PWR 80dB
X: 0Hz + 1.0kHz #A: 256 LIN
SETUP W2

MAIN Y: 3.90E-9V
X: 0Hz



20 COHERENCE
Y: 1.00
X: 0Hz → 1.8kHz
SETUP W2 #A: 256 LIN


MAIN Y:
X: 0Hz 3.72m



Type 2032

Page No.
5

Sign. :



Meas.

Object:


PLF PR 3.1
Ch A = T10
Ch B = M 3

Refs 196

Comments:




② COHERENT POWER PWR 80dB [] INPUT MAIN Y:
Y: 150mV X: 0Hz 3.08E-8VA
X: 0Hz → 1.8kHz
SETUP W2 #A: 256 LIN



Type 2032

Page No.
8

Sign.:



Meas.

Object:

SLF PR 3.1
C_{1A} = T_{1A}
C_{1B} = M_{1A}

Comments:


2 COHERENT POWER PWR 80dB
Y₁ 150mV
X₁ 0Hz + 1.8kHz LIN
SETUP W2 + HA: 256

W20 COHERENCE

Y: 1.00
X: 0Hz + 1.6kHz
SETUP W22 #A: 256 LIN

INPUT

MAIN Y:
X: 944Hz



Type 2032

Page No.
76

Sign.:


Meas.



Object:

PLF PR 3.5
ChA = T10
ChC = M1

P19187

Comments:






W20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1. 6kHz
SETUP W22 #A: 256 LIN

INPUT

X₁ 944Hz 337u



Page No.
80

Sign.:

MAIN X₁ 944Hz 337u
0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k

Meas.

Object:

PLF PR 3.5
Ch A = T16
Ch B = M3

Rdg 187

Comments:




MAIN X₁ 944Hz 43.2E-9uA
0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k

2 COHERENT POWER PWR 80dB
Y₁ 150mV₂ PWR 80dB
X₁ 0Hz + 1. 6kHz LIN
SETUP W22 #A: 256 LIN

W20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256


INPUT MAIN Y:
X: 704Hz 103m



Type 2032

Page No.
82

Sign.:



Meas.

Object:

PIF PR Z
CIA T16
CB 114

Rdg 197

Comments:



MAIN Y:
X: 704Hz

2 COHERENT POWER
Y: 150m² PWR 80dB
X: 0Hz + 1.6kHz LIN
SETUP W22 #A: 256

ORIGINAL PAGE IS
OF POOR QUALITY

APPENDIX E

SAMPLE NARROW-BAND SPECTRA

11 AUTO SPEC CH. A RMS [] INPUT MAIN Y₁ -48.9dB
Y: 20.0dB /1.00V RMS 80dB X: 112Hz
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256

Type 2032

Page No.
15

Sign.:

Meas.



Object:

PLF PR1.2
Ch A = T10
Ch B = M1


Rdg 176

Comments:

10 AUTO SPEC CH. B
Y: 20.0dB /1.00V RMS 80dB X: 112Hz
X: 0Hz + 1.6kHz LIN
SETUP W2 #A: 256 MAIN Y₁ -45.6dB



11 AUTO SPEC CH.A RMS [] INPUT MAIN Y₁ -45.5dB
 Y: 20.0dB / 1.00V RMS 80dB X: MAIN 120Hz
 X: 0Hz + 1.00Hz LIN
 SETUP V2 #A, 256



Type 2032

Page No.
18

Sign.:

Meds.

Objcts:


PLF PR 1.2
 $\frac{CBA = T10}{CBB = M2}$

Rdg 176

Comments:

10 AUTO SPEC CH.B RMS 80dB MAIN Y₁ -37.0dB
 Y: 20.0dB / 1.00V RMS 80dB X: MAIN 120Hz
 X: 0Hz + 1.00Hz LIN
 SETUP V2 #A, 256

11 AUTO SPEC CH. A 20. 0dB / 1. 00V RMS 80dB INPUT MAIN Y₁ 120Hz -45. 4dB
Y: 20. 0dB / 1. 00V RMS 80dB INPUT MAIN Y₁ 120Hz -45. 4dB
X: 0Hz + 1. 6kHz LIN
SETUP W2 #A: 256



Type 2032

Page No.
17
Sign. 1

Meas.
Object:

PLF PR 1.2
 $\frac{G_A = 710}{G_B = 113}$


17176

Comments:



10 AUTO SPEC CH. B 20. 0dB / 1. 00V RMS 80dB INPUT MAIN Y₁ 120Hz -37. 4dB
Y: 20. 0dB / 1. 00V RMS 80dB INPUT MAIN Y₁ 120Hz -37. 4dB
X: 0Hz + 1. 6kHz LIN
SETUP W2 #A: 256

AUTO SPEC CH. A RMS [] INPUT
 Y: 20.0dB /1.00V RMS 80dB MAIN Y: -45.6dB
 X: 0Hz + 1.6kHz LIN
 SETUP W2 #A, 256



Type 2032

Page No.
16

Sign.:

Meas.

Object:

$$\frac{PLF}{ChA} = \frac{710}{114}$$


Rdg 176

Comments:

AUTO SPEC CH. B RMS [] INPUT
 Y: 20.0dB /1.00V RMS 80dB MAIN Y: -33.1dB
 X: 0Hz + 1.6kHz LIN
 SETUP W2 #A, 256

MB AUTO SPEC CH. A RMS [] INPUT HARM Y_i -37. 7dB
Y: 20. 0dB /1. 00V X_i 792Hz
X: 0Hz + 1. 0kHz AX: 396. 0000Hz
SETUP W2 #A: 256

Type 2032



Page No.
127

Sign.:


Meas.
Object:

PLF PR 3.1
 $\frac{C_A}{C_B} = T_{10}$
 $C_B = M_L$



Rig 186

Comments:

MB AUTO SPEC CH. B RMS [] INPUT HARM Y_i -40. 9dB
Y: 20. 0dB /1. 00V X_i 792Hz
X: 0Hz + 1. 0kHz AX: 396. 0000Hz
SETUP W2 #A: 256



11 AUTO SPEC CH. A [] INPUT
 Y: 20. 0dB /1. 00V RMS []
 X: 0Hz + 1. 6kHz LIN 80dB
 SETUP W2 AX: 256



Type 2032

Page No.
3

Sign.:

Meas.
Object:


PLF PR 3.1
Ch A = T10
Ch B = M2

Rdg 186


Comments:

10 AUTO SPEC CH. B
 Y: 20. 0dB /1. 00V RMS 80dB
 X: 0Hz + 1. 6kHz LIN 80dB
 SETUP W2 AX: 256

1.1 AUTO SPEC CH. A RMS [] INPUT
 20. 0dB / 1. 00V RMS 80dB
 Y: 0Hz + 1. 0kHz X:
 X: 0Hz + 1. 0kHz #A: 256
 SETUP W2



Type 2032




Sign.:

Meas.

Object: 1
 $\frac{PLF}{PLA} = \frac{10}{13}$
 $c_n R = M_3$


178



Comments:

ORIGINAL PAGE IS
OF POOR QUALITY

11 AUTO SPEC CH.A RMS [] INPUT HARM Y₁ -37. 8dB
 Y₁ 20. 0dB / 1. 00V X₁ 396Hz
 X₁ 0Hz + 1. 6kHz ΔX₁ 396. 0000Hz
 SETUP W2 #A, 256



Type 2032

Page No.
9

Sign.:

Meds.
Object:

PLF PR 31
 $\frac{Ch\ A = T10}{Ch\ B = M4}$


Rdg 186

Comments:

10 AUTO SPEC CH.B RMS [] INPUT HARM Y₁ -27. 9dB
 Y₁ 20. 0dB / 1. 00V X₁ 396Hz
 X₁ 0Hz + 1. 6kHz ΔX₁ 396. 0000Hz
 SETUP W2 #A, 256

1.1 AUTO SPEC CH. A [] INPUT HARM Y: -45. 0dB
 Y: 20. 0dB /1. 00V RMS X: 362Hz
 X: 0Hz + 1. 8kHz ΔX: 362. 0000Hz
 SETUP V2 KA: 256

Type 2032



Page No.
10

Sign.:

Meas.

Object:

$$\frac{PLF}{ChA} = \frac{PR3.5}{T10}$$

$$ChB = M1$$

Rd9/187

Comments:

1.0 AUTO SPEC CH. B RMS Y: -20. 9dB
 Y: 20. 0dB /1. 00V RMS X: 362Hz
 X: 0Hz + 1. 8kHz ΔX: 362. 0000Hz
 SETUP V2 KA: 256

Type 2032

Page No.
11

Sign.:





Meas.


Object:

PLF PR 3.5
 $ChA = T1G$
 $ChB = M2$

849/187

Comments:






Bruel & Kjaer

11 AUTO SPEC CH. A RMS [] INPUT
Y: 20. 0dB / 1. 00V RMS 80dB
X: 0Hz + 1. 0kHz LIN
SETUP W2 #A: 256

HARM Y: -45. 0dB
X: 362Hz
ΔX: 362. 0000Hz




Mads.
Object:

PF PR 2.5
#A = 716
#B = 112


Fri 1977

Comments:



10 AUTO SPEC CH. B RMS 80dB
Y: 20. 0dB / 1. 00V RMS 80dB
X: 0Hz + 1. 0kHz LIN
SETUP W2 #A: 256


HARM Y: -13. 7dB
X: 362Hz
ΔX: 362. 0000Hz



Brüel & Kjaer

1.1 AUTO SPEC CH. A RMS [] INPUT HARM Y₁ -44. 8dB
Y: 20. 0dB /1. 00V RMS 80dB X₁ 362Hz
X: 0Hz + 1. 0kHz LIN AX: 362. 0000Hz
SETUP W2 #A: 256

Type 2032



Page No.
14

Sign.:


183

Mass.
Object:

PLF PR 3.5
 $\frac{ch A}{ch B} = \frac{T10}{M4}$

Rdg 187

Comments:



1.0 AUTO SPEC CH. B RMS 80dB
Y: 20. 0dB /1. 00V RMS 80dB X₁ 362Hz
X: 0Hz + 1. 0kHz LIN AX: 362. 0000Hz
SETUP W2 #A: 256

1.1 AUTO SPEC CH. A RMS 80dB
Y: 20. 0dB /1. 00V RMS 80dB X₁ 362Hz
X: 0Hz + 1. 0kHz LIN AX: 362. 0000Hz
SETUP W2 #A: 256

APPENDIX F


**COMPARISON OF COHERENCE FUNCTION FOR INTERNAL PRESSURE
TRANSDUCERS NO. 9 AND NO. 10 TO FAR FIELD MICROPHONES
PR=3.5**

APPENDIX F

PART I

TRANSDUCER NO. 10


W20 COHERENCE
Y: 1.00
X: 0Hz + 1.6kHz LIN
SETUP W12 1. #A: 256 LIN



Brüel & Kjaer
Type 2032

Page No.
81 6/17/88

Sign.:



MAIN Y:
X: 1600Hz 1. 20m
W1 FREQ RESP H1 PHASE
Y: -200 TO +200 DEG
X: 0Hz + 1. 6kHz LIN
SETUP W12 #A: 256 LIN

Meas.

Object:

PLT PF 3.5
ChA i10
1000 Hz
100
K10 i38'


Comments:

W20 COHERENCE
 Y: 1.00
 X: 0Hz + 1.6kHz LIN
 SETUP W12 #A: 256

INPUT

MAIN Y: 1.07m
X: 1600Hz

ORIGINAL PAGE IS
OF POOR QUALITY



Type 2032

Page No.
82

Sign.:

187

Meas.
Obj ect,

$DLF PR 3.5$
 $Ch A = T/10$
 $Ch B = M/2$
 $Time 4.124$
 $20ms$
 $Rdg 187$

Comments:

W1 FREQ RESP H1 PHASE
 Y: -200 TO +200 DEG
 X: 0Hz + 1.6kHz LIN
 SETUP W12 #A: 256

MAIN Y: 1.07m
 X: 1600Hz

W20 COHERENCE
Y₁ 1.00
X₁ 0Hz + 1. 6kHz LIN
SETUP W12 #A, 256

INPUT

MAIN
X₁ 1600Hz 1. 06m

Type 2032

Page No.
83

Sign.:




Meas.
Object:


DLF P83.5
Ch A = T/6
Ch B = M3
71ms de/2~
70 ms
Rdg 187



Comments:





ORIGINAL PAGE IS
OF POOR QUALITY





Brüel & Kjær

Type 2032



Page No.
48

Sign.:

APPENDIX F

PART II


TRANSDUCER NO. 9



W2D COHERENCE
Y₁: 1.00
X₁: 0Hz + 1.6kHz LIN
SETUP W12 #A: 256

INPUT


MAIN Y₁: 15.7m
X₁: 684Hz



Type 2032

Page No.
69 6/17/88

Sign.:



Meas.
Object:

PLF PR 3.5
Ch A = T9
Ch B = M2
Time del/dy
9 ms
Rdg/87

Comments:



ORIGINAL PAPER IS
OF POOR QUALITY

W2D COHERENCE
 Y₁: 1.00
 X₁: 0Hz ± 1.6KHz LIN
 SETUP W12 WA: 256


INPUT MAIN Y₁ 29.0m
 X₁ 684Hz

Type 2032
 C.

Page No.
 68 6/11/86

Sign.:

0 0.2k 0.4k 0.6k 0.8k 1.0k 1.2k 1.4k 1.6k



MAIN Y₁
 X₁ 684Hz

W1 FREQ RESP H1 PHASE
 Y₁ -200 TO +200 DEG
 X₁ 0Hz ± 1.6KHz LIN
 SETUP W12 WA: 256


Comments:

F111 PH 2.5
 1.2
 1.3
 1.4
 1.5
 1.6
 1.7
 1.8
 1.9

W2D COHERENCE
Y₁, 1.00
X₁, 0Hz + 1.6KHz LIN
SETUP W12 #A, 256

INPUT

MAIN Y₁ 33.3m
X₁ 684Hz



Type 2032

Page No.
87 6/17/83


Sign.:



195

Mass.
Object:

PLF PR 3.5
Ch A = T9
Ch B = M4
Time delay
0 ms
Fig 187



Comments:



ORIGINAL PAGE IS
OF POOR QUALITY

TABLE I. - AERODYNAMIC DATA FOR ACOUSTIC TESTS


Reading	Pressure ratio	Total temperature, T _{ts} , °R	Total pressure, P _{ts} , psi	Mass flow rate, W, lb/s	Ambient pressure, T _{amb} , °R	Ambient pressure, P _{amb} , psi	Wind direction, deg	Wind velocity, mph
176	1.17	524.5	16.8	32.77	527.7	14.35	178	8
184	1.27	536.7	18.29	43.55	525.9	14.34	161	2
177	1.36	521.8	19.52	46.74	527.3	14.35	153	4
178	1.57	524.2	22.5	57.79	527		180	9
179	1.76	526.4	25.25	66.15	526.8		181	7
188	1.92	535.9	27.61	72.03	526.3		174	10
181	2.2	532.6	31.56	82.53	526.4		170	8
182	2.1	533.7	31.7	82.15	526.1		163	5
183	2.45	537.2	35.12	91.13	526	14.35	179	6
185	2.92	537.6	41.85	109.8	526	14.34	171	5
186	3.01	537.3	43.11	111.5	525.8	14.34	177	7
187	3.45	536.5	49.43	128.5	526.4	14.34	180	9

TABLE II. - OVERALL SOUND PRESSURE LEVEL

[dB reference, 20 mPa.]


Reading number	Pressure ratio	Microphone				Transducer					
		1	2	3	4	5	6	7	8	9	10
		Microphone angle, deg									
		150	135	120	90						
Tape channel numbers											
176	1.2	91.2	92	91.8	92	160.3	158.9	107.5	118.7	107.2	118.7
184	1.3	94	94.3	94.8	94.3	162.6	161	109.6	100.4	108.6	121
177	1.4	95.6	95.6	95.8	94.9	162.7	161.7	110.2	100.2	109	122.1
178	1.6	81.4	99.3	99.3	97.4	164.3	163.9	111.5	100.8	110	123.1
179	1.8	84.1	83.2	82.4	98.6	165.1	164.6	111.8	100.6	111	124
188	2	87.7	85.3	83.8	99.7	163.5	163.1	111	100.5	110.1	122.6
181	2.3	90.1	88.1	85.9	83.8	167.2	166.6	113.7	101.4	112.5	106.9
182	2.3	90.7	87.7	85.4	82.5	166.8	166.7	155	101.6	112.1	106.9
183	2.5	135.3	133.5	131.3	88.6	167.4	167.4	155.8	102	112.8	107.9
185	3	121.3	137.7	135.4	135.5	149.8	149.8	157.3	142.8	155.7	108.7
186	3.1	121.4	138.3	136.5	121.3	150	150.1	157	143	155.5	109.1
187	3.5	122.7	139.6	138.4	123	161.2	160.7	151.9	141.7	150.9	104.2

ORIGINAL PAGE IS
OF POOR QUALITY



(A) OVERALL AERIAL VIEW.


FIGURE 1. - POWERED LIFT FACILITY.



(B) TEST STAND.

FIGURE 1. - CONTINUED.

ORIGINAL PAGE IS
OF POOR QUALITY



(C) STANDARD NOZZLE AS INSTALLED IN THE TEST RIG.

FIGURE 1. - CONCLUDED.





FIGURE 2. - SCHEMATIC OF POWERED LIFT FACILITY.

ORIGINAL PAGE IS
OF POOR QUALITY



(A) FAR FIELD MICROPHONE LOCATIONS.
FIGURE 3. - POWERED LIFT FACILITY INSTRUMENTATION.



FIGURE 3B. - INTERNAL KULITE PRESSURE TRANSDUCERS INSTALLED AT
STATION 5 AND 6 IN THE VERTICAL PIPE SECTION.




FIGURE 3C. - SCHEMATIC SHOWING INTERNAL PRESSURE TRANSDUCER LOCATIONS IN POWERED LIFT FACILITY FOR ACOUSTIC TESTS.






FIGURE 4. - COHERENCE FUNCTION FOR INTERNAL TO FAR FIELD MICROPHONE. INTERNAL TRANSDUCER NUMBER 10, EXTERNAL MICROPHONE NUMBER 4 AT 90° OFF JET AXIS.


ORIGINAL PAGE IS
OF POOR QUALITY



(D) PRESSURE RATIO 2.0.




(E) PRESSURE RATIO 2.5.




(F) PRESSURE RATIO 3.5.

FIGURE 4. - CONCLUDED.




(A) NOZZLE TRANSDUCER NUMBER 10.

FIGURE 5. - COMPARISON OF THIRD OCTAVE SPECTRA UPSTREAM OF THE ELBOWS TO SPECTRA JUST UPSTREAM OF THE NOZZLE.



(B) NOZZLE TRANSDUCER NUMBER 9.

FIGURE 5. - CONTINUED.




(C) COMPARISON OF ALL TRANSDUCER SPECTRA AT NOZZLE PRESSURE RATIO OF 3.5.

FIGURE 5. - CONCLUDED.


ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY



(A) PRESSURE RATIO 1.2.

FIGURE 6. - COMPARISON OF COHERENCE FUNCTION BETWEEN INTERNAL FLUCTUATING PRESSURE (TRANSDUCER NUMBER 10) AND FAR FIELD MICROPHONES AS A FUNCTION OF MICROPHONE ANGULAR LOCATION.




(B) PRESSURE RATIO 1.8.

FIGURE 6. - CONTINUED.

ORIGINAL PAGE IS
OF POOR QUALITY


ORIGINAL PAGE IS
OF POOR QUALITY



(C) PRESSURE RATIO 2.0.

FIGURE 6. - CONTINUED.


ORIGINAL PAGE IS
OF POOR QUALITY



(D) PRESSURE RATIO 2.5.

FIGURE 6. - CONTINUED.


ORIGINAL PAGE IS
OF POOR QUALITY



(E) PRESSURE RATIO 3.0.

FIGURE 6. - CONTINUED.


ORIGINAL PAGE IS
OF POOR QUALITY



(F) PRESSURE RATIO 3.5.


FIGURE 6. - CONCLUDED.

**ORIGINAL PAGE IS
OF POOR QUALITY**




(A) INTERNAL NOISE PROPAGATION FROM COHERENCE FUNCTION,
TRANSDUCER T10-T5.

FIGURE 7. - INTERNAL NOISE COHERENCE FUNCTION, NOISE
FROM UPSTREAM OF MEASURING STATIONS PR 1.2, 3.5.




(B) INTERNAL NOISE PROPAGATION FROM COHERENCE FUNCTION,
TRANSDUCER T10-T7.

FIGURE 7. - CONCLUDED.



(A) SUB AND TRANSONIC JET VELOCITIES.

FIGURE 8. - OVERALL SOUND PRESSURE AS A FUNCTION OF ANGULAR POSITION OFF THE INLET AXIS.




(B) SUPERSONIC JET VELOCITIES.

FIGURE 8. - CONCLUDED.

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY



(A) PRESSURE RATIO 1.2.
FIGURE 9. - COMPARISON OF FAR FIELD NARROW BAND SOUND
PRESSURE LEVEL SPECTRA SHAPES.

ORIGINAL PAGE IS
OF POOR QUALITY






FIGURE 9. - CONCLUDED.




(A) FAR FIELD MICROPHONES.

FIGURE 10. - OVERALL SOUND PRESSURE LEVEL AS A FUNCTION OF NOZZLE PRESSURE RATIO.




(B) INTERNAL PRESSURE TRANSDUCERS.

FIGURE 10. - CONCLUDED.



(A) LOW TO TRANSONIC PRESSURE RATIOS, MICROPHONE AT 90°.



(B) HIGH NOZZLE PRESSURE RATIOS, MICROPHONE AT 90°;

FIGURE 11. - INTERNAL NOISE ONE-THIRD OCTAVE SOUND PRESSURE LEVEL SPECTRA MEASURED IN THE FAR FIELD.







FIGURE 11. - CONTINUED.



(E) LOW TO TRANSONIC PRESSURE RATIOS, MICROPHONE AT 45° .



(F) HIGH NOZZLE PRESSURE RATIOS, MICROPHONE AT 45° .

FIGURE 11. - CONTINUED.

ORIGINAL PAGE IS
OF POOR QUALITY





FIGURE 11. - CONCLUDED.



Report Documentation Page

1. Report No. NASA CR-182217	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle NASA Powered Lift Facility Internally Generated Noise and Its Transmission to the Acoustic Far Field		5. Report Date November 1988	
7. Author(s) Ronald G. Huff		6. Performing Organization Code	
9. Performing Organization Name and Address Sverdrup Technology, Inc. NASA Lewis Research Center Group Cleveland, Ohio 44135		8. Performing Organization Report No. None (E-4464)	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135-3191		10. Work Unit No. 505-62-71	
15. Supplementary Notes Project Manager, Rudolph E. Grey, Propulsion Systems Division, NASA Lewis Research Center. Ronald G. Huff, Ronald G. Huff and Associates, subcontractor to Sverdrup Technology, Inc. (Subcontract Nos. 2717-01-80 and 2717-85, R.M. Nallasamy, Monitor).		11. Contract or Grant No. NAS3-25266	
16. Abstract Noise tests of NASA Lewis Research Center's Powered Lift Facility were performed to determine the frequency content of the internally generated noise that reaches the far field. The sources of the internally generated noise are the burner, elbows, valves, and flow turbulence. Tests over a range of nozzle pressure ratios from 1.2 to 3.5 using coherence analysis revealed that low frequency noise below 1200 Hz is transmitted through the nozzle. Broad banded peaks at 240 and 640 Hz were found in the transmitted noise. Aeroacoustic excitation effects are possible in this frequency range. The internal noise creates a noise floor that limits the amount of jet noise suppression that can be measured on the PLF and similar facilities.			
17. Key Words (Suggested by Author(s)) Facility noise; Jet noise; Core engine noise; Noise floor; Acoustics; Noise pollution		18. Distribution Statement Unclassified - Unlimited Subject Category 09	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No of pages 217	22. Price* A10


National Aeronautics and
Space Administration

Lewis Research Center
Cleveland, Ohio 44135

Official Business
Penalty for Private Use \$300

FOURTH CLASS MAIL

ADDRESS CORRECTION REQUESTED



Postage and Fees Paid
National Aeronautics and
Space Administration
NASA 451

NASA
